

Emergency Contact Information:

AccuStandard, Inc. 1-203-786-5290

SAFETY DATA SHEET

Hours: Monday to Friday 8:00am to 5:00pm EST

SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

1.1 - Product Identifiers

Catalog Name: P-215N

Description: Propachlor

CAS No.: 1918-16-7

1.2 - Relevant Identified Uses of the Substance or Mixture

Laboratory Chemical Reference Material

1.3 - Supplier Details

Company: AccuStandard, Inc. 125 Market St. New Haven, CT 06513 USA

Telephone Number: 203-786-5290

Fax: 203-786-5287

Email: edocs@accustandard.com


1.4 - Emergency Telephone Number

Emergency Phone #: AccuStandard, Inc. 1-203-786-5290 Hours: Monday to Friday 8:00am to 5:00pm EST

SECTION 2 - HAZARDS IDENTIFICATION

2.1 - GHS Label Elements





Signal Word: Danger

Hazard Codes:

H311 - Toxic if absorbed through skin. (Acute toxicity, dermal, category 3)

H315 - Irritating to skin. (Skin corrosion/irritation, category 2)

H335 - May be irritating to mucous membrane and upper respiratory system. (Specific target organ toxicity, single exposure; Respiratory tract irritation, category 3)

H350 - California Proposition 65 Warning: This product contains a component (or components) that may cause cancer in a concentration greater than or equal to 0.1%.

Precautionary Codes:

P202 - This product should only by used by persons trained in the safe handling of hazardous chemicals.

P235 - Store in a cool dry place.

P262 - Do not get in eyes, on skin or clothing.

P264 - Wash thoroughly after handling. Do not take internally. Eye wash and safety equipment should be readily available.

SECTION 2 - HAZARDS IDENTIFICATION - continued

2.1 - GHS Label Elements - continued

P280 - Protective gloves must be worn to prevent skin contact.

P284 - Respiratory Protection: If workplace exposure limit(s) of product or any component is exceeded (see TLV/PEL), or a risk assessment shows air-purifying respirators are appropriate, use of a NIOSH/MSHA approved air supplied respirator is advised. Use a full-face respirator with multi-purpose combination (US) or type ABEK (EN14387) respirator cartridges in absence of proper environmental control. Always use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU). Engineering and/or administrative controls should be implemented to reduce exposure.

P338 - Eye contact: Immediately flush with plenty of water. After initial flushing, remove and contact lenses and continue flushing for at least 15 minutes. Assure adequate flushing by separating the eyelids with fingers.

P360 - Skin contact: Immediately wash skin with soap and plenty of water. Remove contaminated clothing. Get medical attention if symptoms occur. Wash clothing before reuse.

P404 - Store in a tightly closed container.

2.2 - Other Hazards

2.2.1 - Symptom of Exposure Health/Environment

Suspected endocrine toxicant: May cause diseases such as hypothyroidism, diabetes mellitus, hypoglycemia, reproductive disorders, and cancer.

2.2.2 - Potential Health Effects

May be irritating to eyes.

Irritating to skin. (Skin corrosion/irritation, category 2)

Toxic if absorbed through skin. (Acute toxicity, dermal, category 3)

May be irritating to mucous membrane and upper respiratory system. (Specific target organ toxicity, single exposure; Respiratory tract irritation, category 3)

May be harmful if inhaled. (Acute toxicity, inhalation, category 5)

May be harmful if swallowed. (Acute toxicity, oral, category 5)

2.2.3 - Routes of Entry

Inhalation, ingestion or skin contact.

2.2.4 - Carcinogenicity

California Proposition 65 cancer hazard.

California Proposition 65 Warning: This product contains a component (or components) that may cause cancer in a concentration greater than or equal to 0.1%.

SECTION 3 - COMPOSITION / ANALYTES DATA

Description: Propachlor

Synonyms: Propachlor; Ramrod; 2-Chloro-N-isopropylaretanilide Molecular Weight: 211.69 Molecular Formula: C11H14CINO EC#: 217-638-2 Index#: 616-008-00-8

			ACGIH -TLV (mg/m ³)			OSHA -PEL (mg/m ³)		
Analyte	CAS Number	% Concentration	TWA	STEL	Skin	TWA	STEL	Skin
Propachlor	1918-16-7	100.000						

SECTION 4 - FIRST AID MEASURES

4.1 - First Aid Procedures - General

Get medical assistance for all cases of overexposure.

4.2 - Eye Contact

Eye contact: Immediately flush with plenty of water. After initial flushing, remove and contact lenses and continue flushing for at least 15 minutes. Assure adequate flushing by separating the eyelids with fingers. (P338)

4.3 - Skin Contact

Skin contact: Immediately wash skin with soap and plenty of water. Remove contaminated clothing. Get medical attention if symptoms occur. Wash clothing before reuse. (P360)

4.4 - Inhalation

Inhalation: Remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention.

4.5 - Ingestion

Ingestion: Call a physician or poison control center immediately. ONLY induce vomiting at the instructions of a physician. Never give anything by mouth to an unconscious person.

SECTION 5 - FIRE FIGHTING MEASURES

5.1 - Flammable Properties

During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion.

5.2 - Extinguishing Media

Use alcohol foam, carbon dioxide, dry chemical, or water spray when fighting fires involving this material.

5.3 - Protection of Firefighters

As in any fire, wear self-contained breathing apparatus pressure demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

6.1 - Spill Response

Wear a self-contained breathing apparatus and appropriate Personal protection. Prevent contact with skin or eyes. Ventilate area. Avoid raising dust. Take up and containerize for proper disposal. Flush spill area with water. Comply with Federal, State, and local regulations.

SECTION 7 - HANDLING AND STORAGE

Store in a tightly closed container. (P404)

Store in a cool dry place. (P235)

Avoid inhalation.

Use with adequate ventilation.

Do not get in eyes, on skin or clothing. (P262)

Avoid prolonged or repeated exposure.

This product should only by used by persons trained in the safe handling of hazardous chemicals. (P202)

SECTION 8 - EXPOSURE CONTROLS

8.1 - Engineering Controls/PPE

Wash thoroughly after handling. Do not take internally. Eye wash and safety equipment should be readily available. (P264)

8.2 - General Hygene Considerations

Respiratory Protection: If workplace exposure limit(s) of product or any component is exceeded (see TLV/PEL), or a risk assessment shows air-purifying respirators are appropriate, use of a NIOSH/MSHA approved air supplied respirator is advised. Use a full-face respirator with multi-purpose combination (US) or type ABEK (EN14387) respirator cartridges in absence of proper environmental control. Always use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU). Engineering and/or administrative controls should be implemented to reduce exposure.

Protective gloves must be worn to prevent skin contact. (P280)

(Butyl, viton or equivalent)

Safety glasses with side shields must be worn at all times.

Use eye protection tested and approved under the appropriate government standards such as NIOSH (US) or EN 166 (EU).

All recommendations are advisory only and must be evaluated by an industrial hygienist and/or safety officer familiar with the specific situation of anticipated use, such as concentration and amount of the substance in the workplace. Any recommendation should not be construed as offering an approval for any specific use of the product.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Light tan, crystalline solid Odor: N/A Odor Threshold: N/A pH: N/A Melting Point: 171 °F / 77°C Boiling Point: 230 °F / 110°C (0.03 mmHg) Flash Point: 345 °F (174 °C) (coc) Evaporation Rate (Butyl Acetate=1): N/A Flammability Class: N/A Lower Flammability Level: N/A Upper Flammability Level: N/A Vapor Pressure: 10 mPa @ 25°C Vapor Density (Air = 1): N/A Specific Gravity: 1.13 g/cm3 Solubility in Water: 580 mg/L Partition Coefficient: log Kow: 1.6 Autoignition Temperature: N/A Decomposition Temperature: N/A Viscosity: N/A VOC Content: N/A

Percent Volatile: N/A

SECTION 10 - STABILITY AND REACTIVITY

Stability: Stable Materials to Avoid: Oxidizers Bases Hazardous Decomposition: Oxides of carbon and nitrogen; hydrogen chloride gas Hazardous Polymerization: Will not occur Condition to Avoid: Excessive heat

SECTION 11 - TOXICOLOGICAL INFORMATION

Human Health Toxicity

See section 2 for specific toxicological information for the ingredients of this product. LD50 (Oral): Rat - 710 mg/kg LD50 (Dermal) : Rabbit - 380 mg/kg LC50 (Inhalation): N/A WARNING: This product contains chemical(s) known to the state of California to cause cancer. No other information related to the toxicological properties of this product is available at this time.

SECTION 12 - ECOLOGICAL INFORMATION

Environmental Toxicity

By complying with sections 6 and 7 there should be no release to the environment. LC50 (Fish): 0.17 mg/L 96H EC50 (Aquatic Invertebrate): 7.8 mg/L 48H BCF: N/A No other information related to the ecological properties of this product is available at this time.

SECTION 13 - DISPOSAL CONSIDERATIONS

Recycle or incinerate at any EPA approved facility or dispose in compliance with Federal, State and local regulations. Empty containers must be triple-rinsed prior to disposal.

SECTION 14 - TRANSPORT INFORMATION

Transportation Information (DOT/IATA) UN Number: UN2811 UN Shipping Class: 6.1 UN Packing Group: III UN Proper Shipping Name: Toxic solid, organic, n.o.s. (Propachlor) Poison by Inhalation: No Marine Pollutant: No

SECTION 15 - REGULATORY INFORMATION

WARNING: This product contains chemical(s) known to the state of California to cause cancer.

This product is subject to SARA section 313 reporting requirements.

The CAS number of this product is NOT listed on the TSCA Inventory.

SECTION 15 - REGULATORY INFORMATION - continued

For laboratory, research and development use only. Not for manufacturing or commercial purposes.

In addition to federal and state regulations, local regulations may apply. Check with your local regulatory authorities.

SECTION 16 - OTHER INFORMATION

This document has been designed to meet the requirements of OSHA, ANSI, GHS and CHIPs regulations.

The statements contained herein are offered for informational purposes only and are based on technical data that we believe to be accurate. The manufacturer will not assume any liability for the accuracy and completeness of this information. Final determination of the suitability of the material is the responsibility of the user. Although certain hazards are described herein, the user should not presume that these are the only hazards that exist. Since conditions and manner of use are outside of the manufacturers control, we make

NO WARRANTY OF MERCHANTABILITY, EXPRESSED OR IMPLIED, AND ASSUME NO LIABILITY RESULTING FROM ITS USE.

Legend : N/A = Not Available ND = Not Determined NR = Not Regulated

Alteration of any information contained herein without written permission from the manufacturer is strictly prohibited.

HMIS/NFPA HAZARD INDEX

- 0 Minimal
- 1 Slight
- 2 Moderate
- 3 Serious
- 4 Severe
- * Additional Hazard

GHS HAZARD INDEX

Category 1 - Most Severe Category 5 - Least Severe

**** End of Document ****