



# AccuStandard<sup>®</sup>, Inc.

125 Market St., New Haven, CT 06513 USA

Tel: 203-786-5290 Fax: 203-786-5287

## SAFETY DATA SHEET

### SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

#### 1.1 - Product Identifiers

Catalog Name: P-532N

Description: Fosetyl aluminum

#### 1.2 - Relevant Identified Uses of the Substance or Mixture

Laboratory Chemical Reference Material

#### 1.3 - Supplier Details

Company: AccuStandard, Inc.

125 Market St.

New Haven, CT 06513 USA

Telephone Number: 203-786-5290

Fax: 203-786-5287

Email: edocs@accustandard.com

#### 1.4 - Emergency Telephone Number

Emergency Phone #: AccuStandard, Inc.

1-203-786-5290

Hours: Monday to Friday 8:00am to 5:00pm EST

### SECTION 2 - HAZARDS IDENTIFICATION

#### 2.1 - GHS Label Elements



**Signal Word: Warning**

**Hazard Codes:**

H319 - Causes severe eye irritation. (Eye damage/irritation, category 2A)

**Precautionary Codes:**


P202 - This product should only be used by persons trained in the safe handling of hazardous chemicals.

P235 - Store in a cool dry place.

P262 - Do not get in eyes, on skin or clothing.

P264 - Wash thoroughly after handling. Do not take internally. Eye wash and safety equipment should be readily available.

P284 - Respiratory Protection: If workplace exposure limit(s) of product or any component is exceeded (see TLV/PEL), or a risk assessment shows air-purifying respirators are appropriate, use of a NIOSH/MSHA approved air supplied respirator is advised. Use a full-face respirator with multi-purpose combination (US) or type ABEK (EN14387) respirator cartridges in absence of proper environmental control. Always use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU). Engineering and/or administrative controls should be implemented to reduce exposure.



1	HEALTH
0	FLAMMABILITY
0	PHYSICAL HAZARD

**SECTION 2 - HAZARDS IDENTIFICATION** - continued**2.1 - GHS Label Elements** - continued

P338 - Eye contact: Immediately flush with plenty of water. After initial flushing, remove and contact lenses and continue flushing for at least 15 minutes. Assure adequate flushing by separating the eyelids with fingers.

P360 - Skin contact: Immediately wash skin with soap and plenty of water. Remove contaminated clothing. Get medical attention if symptoms occur. Wash clothing before reuse.

P404 - Store in a tightly closed container.

**2.2 - Other Hazards****2.2.1 - Symptom of Exposure Health/Environment**

May cause headache, dizziness, nausea, vomiting, general malaise, muscle twitching, and convulsions.

Symptoms of neurotoxicity may include weakness, tremors, staggered walk or paralysis.

Cholinesterase inhibitor. Can cause heavy salivation and secretion in the lungs, lachrymation, blurred vision, involuntary defecation, diarrhea, tremor, ataxia, sweating, hypothermia, lowered heart rate and/or a fall in blood pressure.

**2.2.2 - Potential Health Effects**

Causes severe eye irritation. (Eye damage/irritation, category 2A)

May be irritating to skin.

May be harmful if absorbed through the skin. (Acute toxicity, dermal, category 5)

Readily absorbed through skin.

Irritating to mucous membrane and upper respiratory system.

May be harmful if inhaled. (Acute toxicity, inhalation, category 5)

May be harmful if swallowed. (Acute toxicity, oral, category 5)

**2.2.3 - Routes of Entry**

Inhalation, ingestion or skin contact.

**2.2.4 - Carcinogenicity**

This product is or contains a component that is not listed (ACGIH, IARC, NTP, OSHA) as a cancer causing agent.

**SECTION 3 - COMPOSITION / ANALYTES DATA**

Description: Fosetyl aluminum

Synonyms: Aluminum tris(O-ethylphosphonate)

Molecular Weight: 354.10

Molecular Formula: C<sub>6</sub>H<sub>18</sub>AlO<sub>9</sub>P<sub>3</sub>

Analyte	CAS Number	% Concentration	ACGIH -TLV (mg/m <sup>3</sup> )			OSHA -PEL (mg/m <sup>3</sup> )		
			TWA	STEL	Skin	TWA	STEL	Skin
Fosetyl aluminium	39148-24-8	100.000	2 (Al)					

**SECTION 4 - FIRST AID MEASURES****4.1 - First Aid Procedures - General**

Get medical assistance for all cases of overexposure.

**4.2 - Eye Contact**

Eye contact: Immediately flush with plenty of water. After initial flushing, remove and contact lenses and continue flushing for at least 15 minutes. Assure adequate flushing by separating the eyelids with fingers. (P338)

**SECTION 4 - FIRST AID MEASURES** - continued**4.3 - Skin Contact**

Skin contact: Immediately wash skin with soap and plenty of water. Remove contaminated clothing. Get medical attention if symptoms occur. Wash clothing before reuse. (P360)

**4.4 - Inhalation**

Inhalation: Remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention.

**4.5 - Ingestion**

Ingestion: Call a physician or poison control center immediately. ONLY induce vomiting at the instructions of a physician. Never give anything by mouth to an unconscious person.

**SECTION 5 - FIRE FIGHTING MEASURES****5.1 - Flammable Properties**

During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion.

**5.2 - Extinguishing Media**

Use alcohol foam, carbon dioxide, dry chemical, or water spray when fighting fires involving this material.

**5.3 - Protection of Firefighters**

As in any fire, wear self-contained breathing apparatus pressure demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

**SECTION 6 - ACCIDENTAL RELEASE MEASURES****6.1 - Spill Response**

Wear suitable protective equipment listed under Exposure Controls / Personal Protection. Eliminate any ignition sources until the area is determined to be free from explosion or fire hazards. Contain the release and eliminate its source, if this can be done without risk. Dispose as hazardous waste. Comply with Federal, State and local regulations.

**SECTION 7 - HANDLING AND STORAGE**

Store in a tightly closed container. (P404)

Store in a cool dry place. (P235)

Avoid inhalation.

Use with adequate ventilation.

Do not get in eyes, on skin or clothing. (P262)

Avoid prolonged or repeated exposure.

This product should only be used by persons trained in the safe handling of hazardous chemicals. (P202)

**SECTION 8 - EXPOSURE CONTROLS****8.1 - Engineering Controls/PPE**

Wash thoroughly after handling. Do not take internally. Eye wash and safety equipment should be readily available. (P264)

**SECTION 8 - EXPOSURE CONTROLS** - continued**8.2 - General Hygiene Considerations**

Respiratory Protection: If workplace exposure limit(s) of product or any component is exceeded (see TLV/PEL), or a risk assessment shows air-purifying respirators are appropriate, use of a NIOSH/MSHA approved air supplied respirator is advised. Use a full-face respirator with multi-purpose combination (US) or type ABEK (EN14387) respirator cartridges in absence of proper environmental control. Always use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU). Engineering and/or administrative controls should be implemented to reduce exposure.

Compatible chemical-resistant protective gloves must be worn to prevent skin contact. Inspect gloves prior to use. Use proper glove removal technique to avoid contact with product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash hands thoroughly and dry.

(Butyl, viton or equivalent)

Use eye protection tested and approved under the appropriate government standards such as NIOSH (US) or EN 166 (EU).

All recommendations are advisory only and must be evaluated by an industrial hygienist and/or safety officer familiar with the specific situation of anticipated use, such as concentration and amount of the substance in the workplace. Any recommendation should not be construed as offering an approval for any specific use of the product.

**SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES**

Appearance: Colorless powder

Odor: N/A

Odor Threshold: N/A

pH: N/A

Melting Point: 215 °C

Boiling Point: Decomposes ~277 °C

Flash Point: N/A

Evaporation Rate (Butyl Acetate=1): N/A

Flammability Class: N/A

Lower Flammability Level: N/A

Upper Flammability Level: N/A

Vapor Pressure: <0.01 mPa @ 25 °C

Vapor Density (Air = 1): N/A

Specific Gravity: 1.53 g/cm<sup>3</sup>

Solubility in Water: 110000 g/L

Partition Coefficient: log Pow: -2.1

Autoignition Temperature: N/A

Decomposition Temperature: N/A

Viscosity: N/A

VOC Content: N/A

Percent Volatile: N/A

**SECTION 10 - STABILITY AND REACTIVITY**

Stability: Stable

Materials to Avoid: Oxidizers

Hazardous Decomposition: Oxides of carbon, aluminum and phosphorous

**SECTION 10 - STABILITY AND REACTIVITY** - continued

Hazardous Polymerization: Will not occur

Condition to Avoid: Excessive heat

**SECTION 11 - TOXICOLOGICAL INFORMATION****Human Health Toxicity**

See section 2 for specific toxicological information for the ingredients of this product.

LD50 (Oral): Rat - >2000 mg/kg

LD50 (Dermal) : Rat - >2000 mg/kg

LC50 (Inhalation): Rat - >5.11 mg/L

No other information related to the toxicological properties of this product is available at this time.

**SECTION 12 - ECOLOGICAL INFORMATION****Environmental Toxicity**

By complying with sections 6 and 7 there should be no release to the environment.

LC50 (Fish): >122 mg/L 96H

EC50 (Aquatic Invertebrate): >100 mg/L 48H

BCF: N/A

No other information related to the ecological properties of this product is available at this time.

**SECTION 13 - DISPOSAL CONSIDERATIONS**

Recycle or incinerate at any EPA approved facility or dispose in compliance with Federal, State and local regulations. Empty containers must be triple-rinsed prior to disposal.

**SECTION 14 - TRANSPORT INFORMATION****Transportation Information (DOT/IATA)**

UN Number: NR

UN Shipping Class: NR

UN Packing Group: NR

UN Proper Shipping Name: Not Regulated for Transport

Poison by Inhalation: No

Marine Pollutant: No

**SECTION 15 - REGULATORY INFORMATION**

The CAS number of this product is NOT listed on the TSCA Inventory.

This product is NOT subject to SARA section 313 reporting requirements.

**For laboratory, research and development use only. Not for manufacturing or commercial purposes.**

In addition to federal and state regulations, local regulations may apply. Check with your local regulatory authorities.

**SECTION 16 - OTHER INFORMATION**

This document has been designed to meet the requirements of OSHA, ANSI, GHS and CHIPs regulations.

The statements contained herein are offered for informational purposes only and are based on technical data that we believe to be accurate. The manufacturer will not assume any liability for the accuracy and completeness of this information. Final determination of the suitability of the material is the responsibility of the user. Although certain hazards are described herein, the user should not presume that these are the only hazards that exist. Since conditions and manner of use are outside of the manufacturers control, we make

**NO WARRANTY OF MERCHANTABILITY, EXPRESSED OR IMPLIED, AND ASSUME NO LIABILITY  
RESULTING FROM ITS USE.**

Legend : N/A = Not Available    ND = Not Determined    NR = Not Regulated

Alteration of any information contained herein without written permission from the manufacturer is strictly prohibited.

**HMIS/NFPA HAZARD INDEX**

- 0 - Minimal
- 1 - Slight
- 2 - Moderate
- 3 - Serious
- 4 - Severe

\* - Additional Hazard

**GHS HAZARD INDEX**

Category 1 - Most Severe  
Category 5 - Least Severe

\*\*\*\* End of Document \*\*\*\*