Emergency Contact Information:

AccuStandard, Inc. 1-203-786-5290

Tel: 203-786-5290 Fax: 203-786-5287 SAFETY DATA SHEET

Hours: Monday to Friday 8:00am to 5:00pm EST

# SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

nc.

# 1.1 - Product Identifiers

Catalog Name: P-306N

Description: Sethoxydim

CAS No.: 74051-80-2

# 1.2 - Relevant Identified Uses of the Substance or Mixture

Laboratory Chemical Reference Material

Standard.

125 Market St., New Haven, CT 06513 USA

# 1.3 - Supplier Details

Company: AccuStandard, Inc. 125 Market St. New Haven, CT 06513 USA

Telephone Number: 203-786-5290

Fax: 203-786-5287

Email: edocs@accustandard.com


# 1.4 - Emergency Telephone Number

Emergency Phone #: AccuStandard, Inc. 1-203-786-5290 Hours: Monday to Friday 8:00am to 5:00pm EST

# **SECTION 2 - HAZARDS IDENTIFICATION**

# 2.1 - GHS Label Elements





HEALTH
FLAMMABILITY
PHYSICAL HAZARD

# Signal Word: Danger

# Hazard Codes:

H331 - Toxic if inhaled. (Acute toxicity, inhalation, category 3)

# **Precautionary Codes:**

P202 - This product should only by used by persons trained in the safe handling of hazardous chemicals.

P262 - Do not get in eyes, on skin or clothing.

P264 - Wash thoroughly after handling. Do not take internally. Eye wash and safety equipment should be readily available.

P280 - Protective gloves must be worn to prevent skin contact.

# **SECTION 2 - HAZARDS IDENTIFICATION** - continued

#### 2.1 - GHS Label Elements - continued

P284 - Respiratory Protection: If workplace exposure limit(s) of product or any component is exceeded (see TLV/PEL), or a risk assessment shows air-purifying respirators are appropriate, use of a NIOSH/MSHA approved air supplied respirator is advised. Use a full-face respirator with multi-purpose combination (US) or type ABEK (EN14387) respirator cartridges in absence of proper environmental control. Always use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU). Engineering and/or administrative controls should be implemented to reduce exposure.

P338 - Eye contact: Immediately flush with plenty of water. After initial flushing, remove and contact lenses and continue flushing for at least 15 minutes. Assure adequate flushing by separating the eyelids with fingers.

P360 - Skin contact: Immediately wash skin with soap and plenty of water. Remove contaminated clothing. Get medical attention if symptoms occur. Wash clothing before reuse.

P404 - Store in a tightly closed container.

#### 2.2 - Other Hazards

2.2.1 - Symptom of Exposure Health/Environment

May cause incoordination, tremor, mental confusion and hyper-excitable state.

2.2.2 - Potential Health Effects

May be irritating to eyes.

May be irritating to skin.

May be harmful if absorbed through the skin. (Acute toxicity, dermal, category 5)

Toxic if inhaled. (Acute toxicity, inhalation, category 3)

May be harmful if swallowed. (Acute toxicity, oral, category 5)

## 2.2.3 - Routes of Entry

Inhalation, ingestion or skin contact.

## 2.2.4 - Carcinogenicity

This product is or contains a component that is not listed (ACGIH, IARC, NTP, OSHA) as a cancer causing agent.

# **SECTION 3 - COMPOSITION / ANALYTES DATA**

Description: Sethoxydim

Synonyms: 2-[1-(Ethoximino)butyl]-5-[2-(ethylthio)-propyl]-3-hydroxy-2-cyclohexen-1-one

Molecular Weight: 327.48

Molecular Formula: C17H29NO3S

			ACGIH -TLV (mg/m <sup>3</sup> )			OSHA -PEL (mg/m <sup>3</sup> )		
Analyte	CAS Number	% Concentration	TWA	STEL	Skin	TWA	STEL	Skin
Sethoxydim	74051-80-2	100.000						

## **SECTION 4 - FIRST AID MEASURES**

## 4.1 - First Aid Procedures - General

Get medical assistance for all cases of overexposure.

### 4.2 - Eye Contact

Eye contact: Immediately flush with plenty of water. After initial flushing, remove and contact lenses and continue flushing for at least 15 minutes. Assure adequate flushing by separating the eyelids with fingers. (P338)

## SECTION 4 - FIRST AID MEASURES - continued

#### 4.3 - Skin Contact

Skin contact: Immediately wash skin with soap and plenty of water. Remove contaminated clothing. Get medical attention if symptoms occur. Wash clothing before reuse. (P360)

# 4.4 - Inhalation

Inhalation: Remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention.

## 4.5 - Ingestion

Ingestion: Call a physician or poison control center immediately. ONLY induce vomiting at the instructions of a physician. Never give anything by mouth to an unconscious person.

# SECTION 5 - FIRE FIGHTING MEASURES

#### 5.1 - Flammable Properties

During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion.

#### 5.2 - Extinguishing Media

Use alcohol foam, carbon dioxide, dry chemical, or water spray when fighting fires involving this material.

#### 5.3 - Protection of Firefighters

As in any fire, wear self-contained breathing apparatus pressure demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

# **SECTION 6 - ACCIDENTAL RELEASE MEASURES**

## 6.1 - Spill Response

Wear suitable protective equipment listed under Exposure Controls / Personal Protection. Eliminate any ignition sources until the area is determined to be free from explosion or fire hazards. Contain the release and eliminate its source, if this can be done without risk. Dispose as hazardous waste. Comply with Federal, State and local regulations.

# **SECTION 7 - HANDLING AND STORAGE**

Store in a tightly closed container. (P404)

Avoid inhalation.

Use with adequate ventilation. (P271)

Do not get in eyes, on skin or clothing. (P262)

Avoid prolonged or repeated exposure.

This product should only by used by persons trained in the safe handling of hazardous chemicals. (P202) Keep refrigerated.

## **SECTION 8 - EXPOSURE CONTROLS**

## 8.1 - Engineering Controls/PPE

Wash thoroughly after handling. Do not take internally. Eye wash and safety equipment should be readily available. (P264)

## SECTION 8 - EXPOSURE CONTROLS - continued

### 8.2 - General Hygene Considerations

Respiratory Protection: If workplace exposure limit(s) of product or any component is exceeded (see TLV/PEL), or a risk assessment shows air-purifying respirators are appropriate, use of a NIOSH/MSHA approved air supplied respirator is advised. Use a full-face respirator with multi-purpose combination (US) or type ABEK (EN14387) respirator cartridges in absence of proper environmental control. Always use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU). Engineering and/or administrative controls should be implemented to reduce exposure.

Material should be handled or transferred in an approved fume hood or with adequate ventilation.

Protective gloves must be worn to prevent skin contact. (P280)

(Butyl, viton or equivalent)

Use eye protection tested and approved under the appropriate government standards such as NIOSH (US) or EN 166 (EU).

All recommendations are advisory only and must be evaluated by an industrial hygienist and/or safety officer familiar with the specific situation of anticipated use, such as concentration and amount of the substance in the workplace. Any recommendation should not be construed as offering an approval for any specific use of the product.

## SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Yellow liquid Odor: Odorless Odor Threshold: N/A pH: N/A Melting Point: N/A Boiling Point: 194 °F / 90 °C Flash Point: N/A Evaporation Rate (Butyl Acetate=1): N/A Flammability Class: N/A Lower Flammability Level: N/A Upper Flammability Level: N/A Vapor Pressure: <0.01 mPa @ 25 °C Vapor Density (Air = 1): N/A Specific Gravity: 1.04 g/cm3 Solubility in Water: 4.7 g/L Partition Coefficient: log Kow: 4.51 Autoignition Temperature: N/A Decomposition Temperature: N/A Viscosity: N/A VOC Content: N/A Percent Volatile: N/A

# SECTION 10 - STABILITY AND REACTIVITY

Stability: Stable Materials to Avoid: Oxidizers Hazardous Decomposition: Oxides of carbon, nitrogen and sulfur

#### SECTION 10 - STABILITY AND REACTIVITY - continued

Hazardous Polymerization: Will not occur Condition to Avoid: Excessive heat

## **SECTION 11 - TOXICOLOGICAL INFORMATION**

## **Human Health Toxicity**

See section 2 for specific toxicological information for the ingredients of this product.

LD50 (Oral): Rat - 2676 mg/kg

LD50 (Dermal) : Rat - >5000 mg/kg

LC50 (Inhalation): Rat - 6.28 mg/L

No other information related to the toxicological properties of this product is available at this time.

## **SECTION 12 - ECOLOGICAL INFORMATION**

#### **Environmental Toxicity**

By complying with sections 6 and 7 there should be no release to the environment. LC50 (Fish): 170 mg/L 96H EC50 (Aquatic Invertebrate): 1.5 mg/L 48H BCF: 22.5 Low potential to bioaccumulate No other information related to the ecological properties of this product is available at this time.

# **SECTION 13 - DISPOSAL CONSIDERATIONS**

Recycle or incinerate at any EPA approved facility or dispose in compliance with Federal, State and local regulations. Empty containers must be triple-rinsed prior to disposal.

# SECTION 14 - TRANSPORT INFORMATION

Transportation Information (DOT/IATA) UN Number: UN2810 UN Shipping Class: 6.1 UN Packing Group: III UN Proper Shipping Name: Toxic liquid, organic, n.o.s. (Sethoxydim) Poison by Inhalation: No Marine Pollutant: No

## **SECTION 15 - REGULATORY INFORMATION**

This product is subject to SARA section 313 reporting requirements.

The CAS number of this product is NOT listed on the TSCA Inventory.

# For laboratory, research and development use only. Not for manufacturing or commercial purposes.

In addition to federal and state regulations, local regulations may apply. Check with your local regulatory authorities.

# **SECTION 16 - OTHER INFORMATION**

This document has been designed to meet the requirements of OSHA, ANSI, GHS and CHIPs regulations.

The statements contained herein are offered for informational purposes only and are based on technical data that we believe to be accurate. The manufacturer will not assume any liability for the accuracy and completeness of this information. Final determination of the suitability of the material is the responsibility of the user. Although certain hazards are described herein, the user should not presume that these are the only hazards that exist. Since conditions and manner of use are outside of the manufacturers control, we make

## NO WARRANTY OF MERCHANTABILITY, EXPRESSED OR IMPLIED, AND ASSUME NO LIABILITY RESULTING FROM ITS USE.

Legend : N/A = Not Available ND = Not Determined NR = Not Regulated

Alteration of any information contained herein without written permission from the manufacturer is strictly prohibited.

# HMIS/NFPA HAZARD INDEX

- 0 Minimal
- 1 Slight
- 2 Moderate
- 3 Serious
- 4 Severe

\* - Additional Hazard

# **GHS HAZARD INDEX**

Category 1 - Most Severe Category 5 - Least Severe

\*\*\*\* End of Document \*\*\*\*