



Page 1/5 Printing date 11/14/2014 Reviewed on 06/17/2014

1: Identification

Product identifier

Product name: Ethylmagnesium chloride, 1-2M in ether

Stock number: 87976

CAS Number: 2386-64-3

Relevant identified uses of the substance or mixture and uses advised against. Identified use: SU24 Scientific research and development

Details of the supplier of the safety data sheet

Details of the supplier of the safety dat Manufacturer/Supplier:
Alfa Aesar, A Johnson Matthey Company Johnson Matthey Catalog Company, Inc. 30 Bond Street
Ward Hill, MA 01835-8099
Tel: 800-343-0660
Fax: 800-322-4757
Email: tech@alfa.com

Email: tech@alfa.com www.alfa.com

Information Department: Health, Safety and Environmental Department

Emergency telephone number: During normal hours the Health, Safety and Environmental Department at (800) 343-0660. After normal hours call Carechem 24 at (866) 928-0789.

2: Hazard(s) identification

Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008



GHS02 Flame

H224 Extremely flammable liquid and vapour. Flam. Lia. 1

Water-react. 1 H260 In contact with water releases flammable gases which may ignite spontaneously.



GHS06 Skull and crossbones

Acute Tox. 3 H301 Toxic if swallowed.



GHS05 Corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

STOT SE 3 H336 May cause drowsiness or dizziness.

Classification according to Directive 67/548/EEC or Directive 1999/45/EC

C: Corrosive

R34: Causes burns.




Xn; Harmful



R22: Harmful if swallowed.



Extremely flammable.



R14/15: Reacts violently with water, liberating extremely flammable gases.

Vapours may cause drowsiness and dizziness. Information concerning particular hazards for human and environment: Causes a narcotic effect. Hazards not otherwise classified No information known.

Labelling according to Regulation (EC) No 1272/2008 The substance is classified and labeled according to the CLP regulation. Hazard pictograms





GHS02 GHS05 GHS06

Signal word Danger
Hazard statements
H224 Extremely flammable liquid and vapour.
H260 In contact with water releases flammable gases which may ignite spontaneously.
H311 Causes severe skin burns and eye damage.
H336 May cause drowsiness or dizziness.
Precautionary statements
P210
Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P301+P361
FSWALLOWED: Immediately call a POISON CENTER/ doctor/

Precautionary statements
P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor/...
P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P405 P501 Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.

WHMIS classification

B2 - Flammable liquid

(Contd. on page 2)

(Contd. of page 1)

Product name: Ethylmagnesium chloride, 1-2M in ether

- Reactive flammable material

D2B - Toxic material causing other toxic effects E - Corrosive material



Classification system HMIS ratings (scale 0-4) (Hazardous Materials Identification System)

HEALTH 3 Health (acute effects) = 3
FIRE 4 Flammability = 4
REACTIVITY 3 Physical Hazard = 3

Other hazards

Results of PBT and vPvB assessment PBT: Not applicable.

vPvB: Not applicable

3: Composition/information on ingredients

Chemical characterization: Substances CAS# Description: 2386-64-3 Ethylmagnesium chloride, 1-2M in ether

4: First-aid measures

Description of first aid measures

General information Immediately remove any clothing soiled by the product.

After inhalation
Supply fresh air. If required, provide artificial respiration. Keep patient warm.
Seek immediate medical advice.

After skin contact
Immediately wash with water and soap and rinse thoroughly.
Seek immediate medical advice.
After eye contact Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing Seek medical treatment. Information for doctor

Most important symptoms and effects, both acute and delayed No further relevant information available. Indication of any immediate medical attention and special treatment needed No further relevant information available.

5: Fire-fighting measures

Extinguishing media

Extinguishing media
Suitable extinguishing agents
Extinguishing powder. Do not use water.
In case of fire, use sand, carbon dioxide or powdered extinguishing agent. Never use water.
For safety reasons unsuitable extinguishing agents Water
Special hazards arising from the substance or mixture
Reacts violently with water
Contact with water releases flammable gases
If this product is involved in a fire, the following can be released:
Carbon monoxide and carbon dioxide
Hydrogen chloride (HCl)
Advice for firefighters
Protective equipment:
Wear self-contained respirator.
Wear fully protective impervious suit.

Wear fully protective impervious suit.

6: Accidental release measures

Personal precautions, protective equipment and emergency procedures
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
Keep away from ignition sources
Environmental precautions:
Do not allow material to be released to the environment without proper governmental permits.
Do not allow product to reach sewage system or any water course.
Do not allow to penetrate the ground/soil.
Methods and material for containment and cleaning up:
Keep away from ignition sources

Keep away from ignition sources. Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Absorb with liquid-binding material (sand, diatomite, acid biliquid-binding material (sand, diatomite, acid biliquid-solution). Use neutralizing agent. Dispose contaminated material as waste according to item 13. Ensure adequate ventilation. Do not flush with water or aqueous cleansing agents Prevention of secondary hazards: Keep away from ignition sources. Reference to other sections

See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

7: Handling and storage

Handling Precautions for safe handling

Precautions for safe handling
Keep container tightly sealed.
Store in cool, dry place in tightly closed containers.
Keep away from heat and direct sunlight.
Ensure good ventilation at the workplace.
Open and handle container with care.
Information about protection against explosions and fires:
Protect from humidity and water.
Protect against electrostatic charges.
Fumes can combine with air to form an explosive mixture.

Fumes can combine with air to form an explosive mixture.

(Contd. on page 3)

Product name: Ethylmagnesium chloride, 1-2M in ether

Keep ignition sources away.

(Contd. of page 2)

Conditions for safe storage, including any incompatibilities

Storage
Requirements to be met by storerooms and receptacles: Store in a cool location.
Information about storage in one common storage facility:
Store away from oxidizing agents.
Store away from alcohols.
Store away from water/moisture.
Further information about storage conditions:
Avoid contact with air/oxygen

Avoid contact with air/oxygen.
Protect from humidity and water.
Keep container tightly sealed.
Store in cool, dry conditions in well sealed containers.
Protect from heat and direct sunlight.
Specific end use(s) No further relevant information available.

8: Exposure controls/personal protection

Additional information about design of technical systems:
Properly operating chemical fume hood designed for hazardous chemicals and having an average face velocity of at least 100 feet per minute.

Control parameters Components with limit values that require monitoring at the workplace:

```
Diethyl ether
```

ppm ACGIH TLV 400; 500-STEL Austria MAK Belgium TWA Denmark TWA 400; 500-STEL 400 400: 500-STEL 400: 500-VLE 400: 300: 600-STEL (skin) 400: 500-STEL 400: 500-STEL Finland TWA France VME

France VME
Germany MAK
Hungary TWA
Ireland TWA
Japan OEL
Korea TLV
Netherlands MAC Korea TLV 400; 500-STEL
Netherlands MAC-TGG 400
Norway TWA 200
Poland TWA 300; 1500-STEL
Russia TWA 400; 300-STEL
Sweden TWA 400; 500-STEL
Switzerland MAK-W 400; 800-KZGUnited Kingdom TWA 400; 500-STE
USA PEL 400
Additional information: No decident 400; 500-STEL

Exposure controls

Personal protective equipment

General protective and hygienic measures
The usual precautionary measures for handling chemicals should be followed.
Keep away from foodstuffs, beverages and feed.
Remove all soiled and contaminated clothing immediately.
Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Maintain an ergonomically appropriate working environment.

Breathing equipment: Use suitable respirator when high concentrations are present.

Protection of hands:

Liquid Dark

Impervious gloves
Check protection of rands.
Impervious gloves
Check protective gloves prior to each use for their proper condition.
The selection of suitable gloves not only depends on the material, but also on quality. Quality will vary from manufacturer to manufacturer.

Eye protection:
Tightly sealed goggles
Full face protection:
Protection: Protective work elething

Body protection: Protective work clothing.

9: Physical and chemical properties

Information on basic physical and chemical properties General Information

Appearance: Form: Color:

Odor: Odor threshold: Not determined Not determined

pH-value:

Change in condition Melting point/Melting range: Boiling point/Boiling range: Sublimation temperature / start: Not determined Not determined

Flash point:

Not determined 44 °C (-47 °F) ((ether)) Not determined. 160 °C (320 °F) ((ether)) Not determined

Not determined

Not determined.

Flammability (solid, gaseous) Ignition temperature: Decomposition temperature: Auto igniting:

Product is not explosive. However, formation of explosive air/vapor mixtures is possible.

Danger of explosion: Explosion limits: Lower: Upper:

1.85 Vol % ((ether)) 36 Vol % ((ether)) Not determined

Vapor pressure: Vapor pressure: Density: Relative density Vapor density

Not determined Not determined Not determined

(Contd. on page 4)

(Contd. of page 3)

Product name: Ethylmagnesium chloride, 1-2M in ether

Evaporation rate Solubility in / Miscibility with Water: Not determined.

Reacts violently

Contact with water releases flammable gases Reacts

Alcohols: Reacts
Partition coefficient (n-octanol/water): Not determined.

Viscosity: dynamic: kinematic: Not determined. Not determined.

Other information No further relevant information available.

10: Stability and reactivity

Reactivity
Reacts violently with water.

Reacts violently with water.
In contact with water releases flammable gases which may ignite spontaneously.

Chemical stability Stable under recommended storage conditions.

Thermal decomposition / conditions to be avoided: Decomposition will not occur if used and stored according to specifications.

Possibility of hazardous reactions

Contact with water releases flammable gases Reacts violently with water

Incompatible materials:

Oxidizing agents Water/moisture

Hazardous decomposition products: Carbon monoxide and carbon dioxide

Hydrogen chloride (HCI) Ethane

11: Toxicological information

Information on toxicological effects

Information on toxicological effects
Acute toxicity:
Harmful if swallowed.
Swallowing will lead to a strong corrosive effect on mouth and throat and to the danger of perforation of esophagus and stomach.
LD/LC50 values that are relevant for classification: No data
Skin irritation or corrosion: Causes severe skin burns.
Eye irritation or corrosion: Causes sevious eye damage.
Sensitization: No sensitizing effects known.
Germ cell mutagenicity: No effects known.
Carcinogenicity: No effects known.
Carcinogenicity: No effects known.
Specific target organ system toxicity - repeated exposure: No effects known.
Specific target organ system toxicity - single exposure: May cause drowsiness or dizziness.
Aspiration hazard: No effects known.
Subacute to chronic toxicity:

Aspiration hazard. No enects known.

Subacute to chronic toxicity:

Diethyl ether is a depressant of the central nervous system and is capable of causing intoxication, drowsiness, stupor and unconsciousness. Severe exposure may cause respiratory failure and death. On contact it may irritate the eyes. Inhalation of magnesium compounds may cause metal fume fever. Metallic magnesium which perforates the skin may cause local lesions. Some magnesium salts have produced muscle weakness, cardiac arrhythmias, respiratory effects and changes in blood chemistry following ingestion.

Subacute to chronic toxicity: No effects known.

Additional toxicological information. To the best of our knowledge the soute and chronic toxicity of this substance is not fully known.

Additional toxicological information: To the best of our knowledge the acute and chronic toxicity of this substance is not fully known.

12: Ecological information

Aquatic toxicity: No further relevant information available.

Persistence and degradability No further relevant information available.

Bioaccumulative potential No further relevant information available.

Mobility in soil No further relevant information available.

Additional ecological information: General notes:

General notes:

Do not allow material to be released to the environment without proper governmental permits.

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Avoid transfer into the environment.

Results of PBT and vPvB assessment

PBT: Not applicable. vPvB: Not applicable

Other adverse effects No further relevant information available.

13: Disposal considerations

Waste treatment methods

Recommendation Consult state, local or national regulations to ensure proper disposal.

Uncleaned packagings:
Recommendation: Disposal must be made according to official regulations.

14: Transport information

UN-Number DOT, IMDG, IATA

UN3399

UN proper shipping name DOT

IMDG, IATA

Organometallic substance, liquid, water-reactive, flammable (ethylmagnesium chloride/diethyl ether)
ORGANOMETALLIC SUBSTANCE, LIQUID, WATER-REACTIVE, FLAMMABLE

(ethylmagnesium chloride/diethyl ether)

(Contd. on page 5)

Product name: Ethylmagnesium chloride, 1-2M in ether (Contd. of page 4) Transport hazard class(es) DOT Class 4.3 Substances which, in contact with water, emit flammable gases. 4.3+3 4.3 (WF1) Substances which, in contact with water, emit flammable gases Label Class ĪMDG, IATA Class 4.3 Substances which, in contact with water, emit flammable gases. 4.3+3 Label Packing group DOT, IMDG, IATA Environmental hazards: Not applicable. Special precautions for user Warning: Substances which, in contact with water, emit flammable gases Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. Transport/Additional information: DOT Marine Pollutant (DOT): No Item: UN3399, Organometallic substance, liquid, water-reactive, flammable (ethylmagnesium chloride/diethyl ether), 4.3 (3), I UN "Model Regulation":

15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

National regulations
All components of this product are listed in the U.S. Environmental Protection Agency Toxic Substances Control Act Chemical substance Inventory.
SARA Section 313 (specific toxic chemical listings) Substance is not listed.
California Proposition 65
Prop 65 - Chemicals known to cause cancer Substance is not listed.
Prop 65 - Developmental toxicity Substance is not listed.
Prop 65 - Developmental toxicity, female Substance is not listed.
Prop 65 - Developmental toxicity, male Substance is not listed.
Prop 65 - Developmental toxicity, male Substance is not listed.
Information about limitation of use: For use only by technically qualified individuals.
Other regulations, limitations and prohibitive regulations
Substance of Very High Concern (SVHC) according to the REACH Regulations (EC) No. 1907/2006. Substance is not listed.
REACH - Pre-registered substances Substance is listed.
Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16: Other information
Employers should use this information only as a supplement to other information gathered by them, and should make independent judgement of suitability of this information to ensure proper use and protect the health and safety of employees. This information is furnished without warranty, and any use of the product not in conformance with this Material Safety Data Sheet, or in combination with any other product or process, is the responsibility of the user.

Department issuing SDS: Health, Safety and Environmental Department.

Department issuing SDS: Health, Safety and Environmental Department.

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

CAS: Chemical Abstracts Service (division of the American Chemical Society)

HMIS: Hazardous Materials Identification System (USA)

WHMIS: Workplace Hazardous Materials Information System (Canada)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

VPUS: very Persistent and very Bioaccumulative

ACGIH: American Conference of Governmental Industrial Hygienists (USA)

OSHA: Occupational Safety and Health Administration (USA)

IATP: National Toxicology Program (USA)

IARC: International Agency for Research on Cancer

EPA: Environmental Protection Agency (USA)

USA