

1 Identification

Product identifier

Product name: Lithium ingot

Stock number: 00658

CAS Number:

7439-93-2

EC number:

231-102-5

Index number:

003-001-00-4

Relevant identified uses of the substance or mixture and uses advised against.

Identified use: SU24 Scientific research and development

Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Alfa Aesar
Thermo Fisher Scientific Chemicals, Inc.
30 Bond Street
Ward Hill, MA 01835-8099
Tel: 800-343-0660
Fax: 800-322-4757
Email: tech@alfa.com
www.alfa.com

Information Department: Health, Safety and Environmental Department

Emergency telephone number:

During normal business hours (Monday-Friday, 8am-7pm EST), call (800) 343-0660. After normal business hours, call Carechem 24 at (866) 928-0789.

2 Hazard(s) identification

Classification of the substance or mixture in accordance with 29 CFR 1910 (OSHA HCS)



GHS02 Flame

Water-react. 1. H260 In contact with water releases flammable gases, which may ignite spontaneously.



GHS05 Corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Hazards not otherwise classified No information known.

Label elements

GHS label elements The product is classified and labeled in accordance with 29 CFR 1910 (OSHA HCS)

Hazard pictograms



GHS02 GHS05

Signal word

Danger

Hazard statements

H260 In contact with water releases flammable gases, which may ignite spontaneously.

H314 Causes severe skin burns and eye damage.

Precautionary statements

P223 Do not allow contact with water.

P231+P232 Handle under inert gas. Protect from moisture.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

WHMIS classification

B6 - Reactive flammable material

D2B - Toxic material causing other toxic effects

E - Corrosive material



Classification system

HMIS ratings (scale 0-4)

(Hazardous Materials Identification System)

HEALTH 3 Health (acute effects) = 3

FIRE 3 Flammability = 3

REACTIVITY 3 Physical Hazard = 3

Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

3 Composition/information on ingredients

Chemical characterization: Substances

CAS# Description:

7439-93-2 Lithium

Concentration: ≤100%

Identification number(s):

EC number: 231-102-5

Product name: *Lithium ingot*

Index number: 003-001-00-4 (Contd. of page 1)

4 First-aid measures
Description of first aid measures
General information Immediately remove any clothing soiled by the product.
After inhalation
Supply fresh air. If required, provide artificial respiration. Keep patient warm.
Seek immediate medical advice.
After skin contact
Immediately wash with water and soap and rinse thoroughly.
Seek immediate medical advice.
After eye contact Rinse opened eye for several minutes under running water. Then consult a doctor.
After swallowing Seek medical treatment.
Information for doctor
Most important symptoms and effects, both acute and delayed Causes severe skin burns.
Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures
Extinguishing media
Suitable extinguishing agents Special powder for metal fires. Do not use water.
For safety reasons unsuitable extinguishing agents Water
Special hazards arising from the substance or mixture
Reacts violently with water
If this product is involved in a fire, the following can be released:
Lithium oxide
Advice for firefighters
Protective equipment:
Wear self-contained respirator.
Wear fully protective impervious suit.

6 Accidental release measures
Personal precautions, protective equipment and emergency procedures
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
Keep away from ignition sources
Environmental precautions: Do not allow product to reach sewage system or any water course.
Methods and material for containment and cleaning up:
Use neutralizing agent.
Dispose of contaminated material as waste according to section 13.
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
Prevention of secondary hazards: Keep away from ignition sources.
Reference to other sections
See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
Protective Action Criteria for Chemicals
PAC-1: 3.3 mg/m3
PAC-2: 36 mg/m3
PAC-3: 220 mg/m3

7 Handling and storage
Handling
Precautions for safe handling
Keep container tightly sealed.
Store in cool, dry place in tightly closed containers.
Ensure good ventilation at the workplace.
Information about protection against explosions and fires: No information known.
Conditions for safe storage, including any incompatibilities
Storage
Requirements to be met by storerooms and receptacles: No special requirements.
Information about storage in one common storage facility:
Store away from water/moisture.
Do not store together with acids.
Store away from oxidizing agents.
Further information about storage conditions:
Protect from humidity and water.
Keep container tightly sealed.
Store in cool, dry conditions in well sealed containers.
Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection
Additional information about design of technical systems:
Properly operating chemical fume hood designed for hazardous chemicals and having an average face velocity of at least 100 feet per minute.
Control parameters
Components with limit values that require monitoring at the workplace:
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
Additional information: No data
Exposure controls
Personal protective equipment
General protective and hygienic measures
The usual precautionary measures for handling chemicals should be followed.
Keep away from foodstuffs, beverages and feed.
Remove all soiled and contaminated clothing immediately.
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.
Maintain an ergonomically appropriate working environment.
Breathing equipment: Use suitable respirator when high concentrations are present.

Product name: Lithium ingot

(Contd. of page 2)

Recommended filter device for short term use:
Use a respirator with type P100 (USA) or P3 (EN 143) cartridges as a backup to engineering controls. Risk assessment should be performed to determine if air-purifying respirators are appropriate. Only use equipment tested and approved under appropriate government standards.

Protection of hands:
Impervious gloves
Check protective gloves prior to each use for their proper condition.
The selection of suitable gloves not only depends on the material, but also on quality. Quality will vary from manufacturer to manufacturer.
Material of gloves Nitrile rubber, NBR
Penetration time of glove material (in minutes) 480

Glove thickness: 0.11 mm
Eye protection:
Tightly sealed goggles
Full face protection
Safety glasses with side shields / NIOSH (US) or EN 166(EU)
Body protection: Protective work clothing.

9 Physical and chemical properties

Information on basic physical and chemical properties

General Information

Appearance:

Form: Solid in various forms
Odor: Odorless
Odor threshold: Not determined.

pH-value: Not applicable.

Change in condition

Melting point/Melting range: 180.5 °C (357 °F)
Boiling point/Boiling range: 1342 °C (2448 °F)
Sublimation temperature / start: Not determined
Flammability (solid, gaseous) Contact with water liberates extremely flammable gases.
Ignition temperature: Not determined
Decomposition temperature: Not determined
Auto igniting: Not determined.

Danger of explosion: Not determined.
Explosion limits:
Lower: Not determined
Upper: Not determined
Vapor pressure at 20 °C (68 °F): 0 hPa
Density at 20 °C (68 °F): 0.53 g/cm³ (4.423 lbs/gal)
Relative density Not determined.
Vapor density Not applicable.
Evaporation rate Not applicable.
Solubility in / Miscibility with
Water: Reacts violently
Contact with water releases flammable gases
Partition coefficient (n-octanol/water): Not determined.
Viscosity:
dynamic: Not applicable.
kinematic: Not applicable.
Other information No further relevant information available.

10 Stability and reactivity

Reactivity

Reacts violently with water.
In contact with water releases flammable gases, which may ignite spontaneously.
Chemical stability Stable under recommended storage conditions.
Thermal decomposition / conditions to be avoided: Decomposition will not occur if used and stored according to specifications.
Possibility of hazardous reactions
Reacts with strong oxidizing agents
Contact with water releases flammable gases
Reacts violently with water
Conditions to avoid No further relevant information available.
Incompatible materials:
Acids
Oxidizing agents
Water/moisture
Hazardous decomposition products: Lithium oxide

11 Toxicological information

Information on toxicological effects

Acute toxicity:

Swallowing will lead to a strong corrosive effect on mouth and throat and to the danger of perforation of esophagus and stomach.
The Registry of Toxic Effects of Chemical Substances (RTECS) contains acute toxicity data for this substance.

LD/LC50 values that are relevant for classification: No data

Skin irritation or corrosion: Causes severe skin burns.

Eye irritation or corrosion: Causes serious eye damage.

Sensitization: No sensitizing effects known.

Germ cell mutagenicity: The Registry of Toxic Effects of Chemical Substances (RTECS) contains mutation data for this substance.

Carcinogenicity: No classification data on carcinogenic properties of this material is available from the EPA, IARC, NTP, OSHA or ACGIH.

Reproductive toxicity: The Registry of Toxic Effects of Chemical Substances (RTECS) contains reproductive data for this substance.

Specific target organ system toxicity - repeated exposure: No effects known.

Specific target organ system toxicity - single exposure: No effects known.

Aspiration hazard: No effects known.

Subacute to chronic toxicity: The Registry of Toxic Effects of Chemical Substances (RTECS) contains multiple dose toxicity data for this substance.

Additional toxicological information: To the best of our knowledge the acute and chronic toxicity of this substance is not fully known.

Product name: **Lithium ingot**

(Contd. of page 3)




12 Ecological information

Toxicity
Aquatic toxicity: No further relevant information available.
Persistence and degradability No further relevant information available.
Bioaccumulative potential No further relevant information available.
Mobility in soil No further relevant information available.
Additional ecological information:
General notes: Avoid transfer into the environment.
Results of PBT and vPvB assessment
PBT: Not applicable.
vPvB: Not applicable.
Other adverse effects No further relevant information available.



13 Disposal considerations

Waste treatment methods
Recommendation Consult state, local or national regulations to ensure proper disposal.
Uncleaned packagings:
Recommendation: Disposal must be made according to official regulations.

14 Transport information

UN-Number DOT, IMDG, IATA	UN1415
UN proper shipping name DOT ADR IMDG, IATA	Lithium 1415 Lithium LITHIUM
Transport hazard class(es) DOT  Class Label ADR  Class Label IMDG, IATA  Class Label	4.3 Substances which, in contact with water, emit flammable gases 4.3 4.3 (W2) Substances which, in contact with water, emit flammable gases 4.3 4.3 Substances which, in contact with water, emit flammable gases 4.3
Packing group DOT, ADR, IMDG, IATA	I
Environmental hazards:	Not applicable.
Special precautions for user EMS Number: Stowage Category Handling Code Segregation Code	Warning: Substances which, in contact with water, emit flammable gases F-G, S-N E H1 Keep as dry as reasonably practicable SG26 In addition: from goods of classes 2.1 and 3 when stowed on deck of a containership a minimum distance of two container spaces athwartship shall be maintained, when stowed on ro-ro ships a distance of 6 m athwartship shall be maintained. SG35 Stow "separated from" acids.
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information: DOT Quantity limitations Marine Pollutant (DOT): <hr/> IMDG Limited quantities (LQ) Excepted quantities (EQ)	On passenger aircraft/rail: Forbidden On cargo aircraft only: 15 kg No 0 Code: E0 Not permitted as Excepted Quantity
UN "Model Regulation":	UN 1415 LITHIUM, 4.3, I

15 Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture
GHS label elements The product is classified and labeled in accordance with 29 CFR 1910 (OSHA HCS)
Hazard pictograms

GHS02 GHS05
Signal word Danger

(Contd. on page 5)
USA

Product name: *Lithium ingot*

(Contd. of page 4)

Hazard statements

H260 In contact with water releases flammable gases, which may ignite spontaneously.
H314 Causes severe skin burns and eye damage.

Precautionary statements

P223 Do not allow contact with water.
P231+P232 Handle under inert gas. Protect from moisture.
P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P405 Store locked up.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

National regulations

All components of this product are listed in the U.S. Environmental Protection Agency Toxic Substances Control Act Chemical substance Inventory.
All components of this product are listed on the Canadian Domestic Substances List (DSL).

SARA Section 313 (specific toxic chemical listings) Substance is not listed.

California Proposition 65

Prop 65 - Chemicals known to cause cancer Substance is not listed.

Prop 65 - Developmental toxicity Substance is not listed.

Prop 65 - Developmental toxicity, female Substance is not listed.

Prop 65 - Developmental toxicity, male Substance is not listed.

Information about limitation of use: For use only by technically qualified individuals.

Other regulations, limitations and prohibitive regulations

Substance of Very High Concern (SVHC) according to the REACH Regulations (EC) No. 1907/2006. Substance is not listed.

The conditions of restrictions according to Article 67 and Annex XVII of the Regulation (EC) No 1907/2006 (REACH) for the manufacturing, placing on the market and use must be observed.

Substance is not listed.

Annex XIV of the REACH Regulations (requiring Authorisation for use) Substance is not listed.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

Employers should use this information only as a supplement to other information gathered by them, and should make independent judgement of suitability of this information to ensure proper use and protect the health and safety of employees. This information is furnished without warranty, and any use of the product not in conformance with this Safety Data Sheet, or in combination with any other product or process, is the responsibility of the user.

Department issuing SDS: Global Marketing Department

Date of preparation/Revision: Print date, revision date and version number are in the header of each page.

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

HMIS: Hazardous Materials Identification System (USA)

WHMIS: Workplace Hazardous Materials Information System (Canada)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative

ACGIH: American Conference of Governmental Industrial Hygienists (USA)

OSHA: Occupational Safety and Health Administration (USA)

NTP: National Toxicology Program (USA)

IARC: International Agency for Research on Cancer

EPA: Environmental Protection Agency (USA)

Water-react. 1: Substances and mixtures which in contact with water emit flammable gases – Category 1

Skin Corr. 1B: Skin corrosion/irritation – Category 1B