EREZTECH LLC



11555 Medlock Bridge Road, Suite 100, Johns Creek, GA 30097, USA

T: +1.888.658.1221 F: 1.678.619.2020

E: info@ereztech.com W: https://ereztech.com

SAFETY DATA SHEET

Section 1. Identification

Iron(III) tert-butoxide dimer **Product Name:**

Solid **Product Type:**

620945-29-1 **CAS Number:**

FE5291 **Product Number:**

Product Manufacturer: Ereztech LLC

11555 Medlock Bridge Road, Suite 100

Johns Creek, GA 30097

Product Information: (888) 658-1221

CHEMTREC: 1-800-424-9300 (USA); In Case of an Emergency:

+1 703-527-3887 (International); CCN836180 *** Contact manufacturer for all non-emergency calls.

Section 2. Hazards Identification

Brown powder, odor not determined. Appearance/Odor: Classification:

FLAMMABLE SOLID – Category 1, H228

SKIN CORROSION/IRRITATION; - Category 2, H315

SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2A, H319 SPECIFIC ORGAN TOXICITY, SINGLE EXPOSURE; RESPIRATORY

TRACT IRRITATION; - Category 3, H335

GHS Label Elements Hazard Pictograms:





WARNING. **Signal Word:**

Hazard Statements: H228: Flammable solid.

H315: Causes skin irritation.

H319: Causes serious eye irritation. H335: May cause respiratory irritation.

Section 2. Hazards Identification

Precautionary Statements

Prevention: P210: Keep away from heat/sparks/open flames/hot surfaces. –

No smoking.

P240: Ground/Bond container and receiving equipment.

P241: Use explosion proof electrical/ventilating/lighting/processing

equipment.

P261: Avoid breathing dust.

P264: Wash skin thoroughly after handling.

P271: Use only outdoors or in a well-ventilated area.

P280: Wear protective gloves/ protective clothing/ eye protection/

face protection.

Response: P302 + P352: IF ON SKIN: Wash with plenty of soap and water.

P304 + P340: IF INHALED: Remove victim to fresh air and keep at

rest in a position comfortable for breathing.

P305 + P351 + P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present.

Continue rinsing.

P312: Call a POISON CENTER or doctor/physician if you feel

unwell.

P332 + P313: If skin irritation occurs: Get medical

advice/attention.

P337 + P313: If eye irritation persists: Get medical

advice/attention.

P362: Take off contaminated clothing and wash before reuse.

P370 + P378: IN case of fire: Use CO₂, dry chemical or foam for

extinction.

Storage: P403 + P233: Store in a well ventilated place. Keep container

tightly closed.

P405: Store locked up.

Disposal: P501: Dispose of contents/ container to an approved wasted

disposal plant.

OSHA/HCS Status: This material is considered hazardous by the OSHA Hazard

Communication Standard (29 CFR 1910.1200).

None identified.

Hazards Not Otherwise Classified (HNOC):

Section 3. Composition/Information on Ingredients

Substances

Formula : $C_{24}H_{54}Fe_2O_6$ Molecular Weight : 275.18 g/mol CAS-No. : 620945-29-1

Synonyms : Iron(III) tert-butoxide; iron(III) t-butoxide

<u>Ereztech FE5291</u> Page 2 of 14 Revision: 1.11

Date of Issue: 4/9/2020

Section 3. Composition/Information on Ingredients

Ingredient Name	%	CAS Number
Iron(III) tert-butoxide dimer	≥ 98	620945-29-1

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First Aid Measures

Description of Necessary First Aid Measures

Move out of dangerous area. Call a POISON CENTER or doctor/physician General Advice:

immediately if symptoms develop or if you feel unwell. Show this safety data

sheet to the doctor in attendance.

Immediately flush eyes with plenty of water, occasionally lifting the upper and **Eye Contact:**

lower eyelids. Check for and remove any contact lenses. Continue rinsing. Seek

medical attention if eye irritation develops and persists.

Skin Contact: Take off contaminated clothing and shoes immediately. Wash off contaminated

skin with soap and plenty of water. Seek medical attention if irritation develops

and persists, if symptoms develop or if you feel unwell.

Inhalation: Remove victim to fresh air and keep at rest in a position comfortable for

> breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If

unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or

waistband. Call a physician or POISON CONTROL CENTER if symptoms develop

or if you feel unwell.

Rinse mouth. Do NOT induce vomiting. Remove dentures if any. If vomiting **Ingestion:**

> occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open

airway. Loosen tight clothing such as a collar, tie, belt or waistband. Call a physician or POISON CONTROL CENTER if symptoms develop or if you feel

unwell.

Most Important Symptoms/Effects, Acute and Delayed Potential Acute Health Effects

Symptoms may include stinging, tearing, redness, swelling and blurred vision. **Eye Contact:**

Inhalation: Product may be irritating to respiratory system. Symptoms may include

coughing, sneezing with phlegm production, sore throat, nausea, headache,

vomitina.

Symptoms may include an itching or burning sensation, reddening, swelling and **Skin Contact:**

blistering with tissue necrosis.

Section 4. First Aid Measures

Ingestion: Product may be expected to be irritating to mucous membranes. Symptoms may

include cramping, localized pain, headache, nausea and vomiting.

Indication of Immediate Medical Attention and Special Treatment Needed, If Necessary

Notes to Physician: Treat symptomatically.

Specific Treatments: No specific treatment.

Protection of First Responders: No action taken shall be taken involving any personal risk

without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See Toxicological Information (Section 11)

Section 5. Fire Fighting Measures

General Hazards: None identified.

Suitable Extinguishing Media: THE MOST EFFECTIVE FIRE EXTINGUISHING AGENT IS DRY

CHEMICAL POWDER PRESSURIZED WITH NITROGEN. For small fires, vermiculite, sand, dry chemical or carbon dioxide (CO_2) may also be used. For large fires, large quantities of water (flooding) may be applied as a spray or a mist to

control the fire and cool affected containers.

Unsuitable Extinguishing Media: None identified.

Unusual Fire and This material reacts slowly with water and compounds containing active hydrogen such as alcohols and acids to

produce t-butanol. Product runoff to sewer may create a fire or explosion hazard. T-butanol vapor/gas is heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to an

ignition source and flashback.

Product of Combustion: Decomposition products include carbon oxides (CO_X) and iron

oxide. Irritating fumes and organic acid vapors may be generated during exposure to elevated temperatures or open

flame.

Protection of Firefighters: Promptly isolate the scene by removing all persons from the

vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Avoid contact with skin or eyes. Avoid breathing dusts,

aerosols, vapors and gases.

Eliminate all local and distant ignition sources. Move containers from fire area if process can be accomplished

without risk to firefighters.

Section 5. Fire Fighting Measures

Protection of Firefighters (cont.):

To reduce the possibility of explosion, use a water spray or fog to reduce direct vapors and to cool unopened containers. Do not cut, grind, drill or weld on or near product containers (even empty) of this product because an explosion may result.

Fire-fighters should wear appropriate protection equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in a positive pressure mode.

Section 6. Accidental Release Measures

Personal Precautions, Protective Equipment and Emergency Procedures

For Non-Emergency Personnel:

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid dust and aerosol formation. Avoid the formation and inhalation of dusts, aerosols and vapors. Provide adequate ventilation. Wear respiratory protection. Put on appropriate personal protective equipment.

For Emergency Responders:

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For Non-Emergency Personnel".

Environmental Precautions:

Do not allow dispersal of spilled material and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods for Containment

General:

Eliminate all local and distant ignition sources. Move containers from spill area if safe to do so. Use spark-proof tools and explosion-proof equipment.

Small Spill:

Contain and collect spillage with non-combustible, dry binding material (e.g. sand, earth, vermiculite or diatomaceous earth) and place in dry, sealed container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor.

Large Spill:

Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas.

Ereztech FE5291 Page 5 of 14 Revision: 1.11

Section 6. Accidental Release Measures

Large Spill (cont.):

Contain and collect spillage with non-combustible, dry binding material (e.g. sand, earth, vermiculite or diatomaceous earth) and place in dry, sealed container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product.

Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and Storage

Precautions:

Product is moisture sensitive; handle under a dry, inert gas. Nitrogen with less than 5 ppm each of moisture and oxygen is recommended. Keep away from all sources of ignition – NO SMOKING. Avoid formation and inhalation of dusts and aerosols. Keep container tightly sealed. Avoid contact with skin, eyes and clothing. Do not ingest. Avoid prolonged exposure. Ensure adequate ventilation.

Protective Measures:

Put on appropriate personal protective equipment (see Section 8). Keep in the original container kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

General Occupational Hygiene:

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Safe Storage Conditions:

Product is moisture sensitive; store under an inert gas.

Nitrogen with less than 5 ppm each of moisture and oxygen is recommended. Keep away from all sources of ignition – NO SMOKING. Store in original container protected from direct sunlight in a dry and well-ventilated area, away from incompatible materials and food and drink. Keep container tightly closed and sealed until ready for use. Store locked up.

Section 8. Exposure Controls/Personal Protection

Introductory Remarks: These recommendations provide general guidance for handling

this product. Because work environments and material handling practices vary, safety procedures should be developed for each

intended application. While developing safe handling

procedures, do not overlook the need to clean equipment and conduct regular repairs. Waste from these procedures should

be handled in accordance with Section 13.

Occupational Exposure Limits: Product contains no substances with occupational exposure

limit values.

Engineering Controls: Properly operating explosion-proof, chemical fume hood

designed for hazardous chemicals and having an average face

velocity of at least 100 feet per minute. Provide an

eyewash/shower station.

Environmental Exposure Controls: Emissions from ventilation or work process equipment should

be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable

levels.

Individual Protection Measures

Hygiene Measures:

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Remove all soiled and contaminated clothing immediately. Do not inhale dusts or aerosols. Avoid contact with eyes and skin. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/Face Protection:

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to aerosols or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles, faceshield (8-inch minimum). Refer to 29 CFR 1910.133, ANSI Z87.1, or European Standard EN166.

Skin Protection

Hand Protection: Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling

chemical products if a risk assessment indicates this is

necessary.

Section 8. Exposure Controls/Personal Protection

Hand Protection (cont.):

Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: Chemical-resistant gloves. For full contact, wear Neoprene or nitrile rubber gloves.

Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Other Skin Protection:

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory Protection:

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multipurpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Section 9. Physical and Chemical Properties

Physical State: Powder.
Color: Brown.

Odor:

Odor Threshold:

PH:

No data available.

Flash Point:

No data available.

No data available.

No data available.

Ereztech FE5291 Page 8 of 14 Revision: 1.11

Section 9. Physical and Chemical Properties

No data available. **Relative Density: Vapor Pressure:** No data available. No data available. **Vapor Density:**

Insoluble. Reacts slowly to release t-butanol. **Water Solubility:**

Section 10. Stability and Reactivity

Reacts slowly with water to release t-butanol. **Reactivity:**

This product is stable when stored under a dry, inert **Chemical Stability:**

> atmosphere and away from heat. Nitrogen containing less than 5 ppm each moisture and air is recommended. This

product is not sensitive to impact.

Conditions to Avoid: Exposure to water/moisture, sources of ignition (heat,

flames, sparks, electrostatic discharge), extremes of

temperature and direct sunlight.

Water, compounds containing active hydrogen (alcohols, **Incompatible Materials:**

acids) and strong oxidizing agents.

Hazardous Decomposition Products: Under normal conditions of storage and use, hazardous

decomposition products should not be produced. Hazardous decomposition products formed under fire conditions: organic acid vapors, t-butanol, carbon oxides and iron oxide fumes. Irritating fumes and organic acid vapors may be generated during exposure to elevated temperatures or open flame. In the event of a fire: see

section 5.

Possibility of Hazardous Reactions: Under normal conditions of storage and use noted above,

hazardous reactions will not occur. Hazardous reactions or instability may occur under certain conditions of storage or use. In contact with water, product releases

flammable vapors.

Section 11. Toxicological Information

Information on Toxicological Effects

Acute Toxicity

Irritation/Corrosion

Sensitization

Germ Cell Mutagenicity

: No specific data available.

: Product causes skin irritation and serious eye irritation.

: No specific data available.

: No effects known.

Section 11. Toxicological Information

(a	rcin	OG C	enity
Cu		UHC	HILLY

IARC

ACGIH

NTP

OSHA

Reproductive Toxicity

Teratogenicity

Specific Target Organ Toxicity (Single Exposure)

Specific Target Organ Toxicity (Repeated Exposure)

Aspiration Hazard

Information on the Likely Routes of Exposure

Additional Information

- : No component of this product present at levels greater than 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
- : No component of this product present at levels greater than 0.1% is identified as probable, possible or confirmed human carcinogen by ACGIH.
- : No component of this product present at levels greater than 0.1% is identified as probable, possible or confirmed human carcinogen by NTP.
- : No component of this product present at levels greater than 0.1% is identified as probable, possible or confirmed human carcinogen by OSHA.
- : This product is not expected to cause reproductive or developmental effects.
- : No specific data available.
- : Inhalation May cause respiratory tract irritation.
- : No specific data available.
- : No specific data available.
- : Common routes of exposure: inhalation (failure to prevent dust formation), dermal (failure to use skin protection), eye (failure to use safety eyewear). Less common: ingestion (failure to employ recommended hygiene measures (e.g. smoking after handling product without washing hands or using hand protection).
- : May be harmful if inhaled, ingested or absorbed through the skin.

To the best of our knowledge, the chemical, physical and toxicological properties of this product have not been thoroughly investigated.

Section 12. Ecological Information

Numerical Measures of Toxicity

Toxicity to Fish

Toxicity to Daphnia and Other Aquatic Invertebrates

Toxicity to Algae

No specific data available.

: No specific data available.

: No specific data available.

Ereztech FE5291 Page 10 of 14 Revision: 1.11

Section 12. Ecological Information

Persistence and Degradability

Biodegradability

Bioaccumulative Potential

Mobility in Soil

Other Adverse Effects

- : No specific data available.
- : No specific data available.
- : No specific data available.
- : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Section 13. Disposal Considerations

Waste Treatment Methods

Product Dispose of in accordance with local, state, and federal

regulations. Refer to 40 CFR 260-299 for complete waste

disposal regulations. Consult your local, state, or federal agency

before disposing of any chemicals.

Contaminated Packaging Empty containers retain product residue (dusts, liquids, vapors

and gases) and can be dangerous. Dispose of as unused product. DO NOT EXPOSE OPENED/EMPTY CONTAINERS TO

MOISTURE/WATER, HEAT, FLAME, SPARKS, STATIC

ELECTRICITY, OR OTHER SOURCES OF IGNITION; THEY MAY

EXPLODE AND CAUSE INJURY OR DEATH.

Section 14. Transport Information

and the second second	DOT	IMDG	IATA
UN Number	UN 3181	UN 3181	UN 3181
UN Proper Shipping	Metal salts of organic	METAL SALTS OF	Metal salts of organic
Name	compounds,	ORGANIC	compounds,
	flammable, n.o.s.	COMPOUNDS,	flammable, n.o.s.
	(Iron(III) tert-butoxide	FLAMMABLE, N.O.S.	(Iron(III) tert-butoxide
	dimer)	(Iron(III) tert-butoxide	dimer)
		dimer)	
Transport Hazard	4.1	4.1	4.1
Classes			
Packing Group	III	III	III
Environmental Hazards	No	No	No
Additional Information	-	-	-

Special Precautions for User

: Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Section 14. Transport Information

Transporting in Bulk According: Not applicable. to Annex II of MARPOL 73/78 and the IBC Code

Section 15. Regulatory Information

TSCA (Toxic Substance Control Act):

This product is not listed on the U.S. Toxic Substances Control Act Chemical Inventory (TSCA Inventory). Use of this product is restricted to research and development only. This product must be used under the supervision of a technically qualified individual as defined by the TSCA. This product must not be used for commercial purposes or in formulations for commercial purposes.

SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Components

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

SARA 311/312 Hazards

Fire Hazard (Flammable Solid), Acute Health Hazard (Skin corrosion or irritation; Serious eye damage or eye irritation; Specific target organ toxicity, single exposure: respiratory irritation).

Massachusetts Right to Know Components

No components are subject to Massachusetts Right to Know Act

Pennsylvania Right to Know Components

No components are subject to Massachusetts Right to Know Act

New Jersey Right to Know Components

No components are subject to Massachusetts Right to Know Act

California Proposition 65 Components

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

Section 16. Other Information

National Fire Protection Association (U.S.A.)



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

HMIS Rating

HEALTH	2
FLAMMABILITY	2
PHYSICAL HAZARD	0

History

Date of Printing : 4/9/2020
Date of Issue/Date of Revision : 4/9/2020
Date of Previous Issue : 1/28/2020
References : None available.

Abbreviations and Acronyms

ACGIH: American Conference of Governmental Industrial Hygienists.

ATE: Acute Toxicity Estimate

CAS: Chemical Abstracts Service (division of the American Chemical Society).

DOT: US Department of Transportation.

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

HMIS: Hazardous Materials Identification System.

HNOC: Hazards Not Otherwise Classified.

IARC: International Agency for Research on Cancer.

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA).

Section 16. Other Information

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA). IDLH: Immediately Dangerous to Life or Health (US National Institute for Occupation Health and Safety (NIOSH)).

IMDG: International Maritime Code for Dangerous Goods.

NFPA: National Fire Protection Association.

NIOSH: National Institute of Occupational Safety and Health.

NTP: National Toxicology Program.

OSHA: Occupational Safety and Health Administration.

PEL: Permissible Exposure Limits. REL: Recommended Exposure Limits.

SARA: Superfund Amendments and Reauthorization Act.

STOT: Specific Target Organ Toxicity. TLV: Threshold Limit Values (ACGIH).

TWA: Time Weighted Average. VOC: Volatile Organic Compound.

Disclaimer

The information herein is believed to be accurate and is presented in good faith; however, no warranties or representations are made by Ereztech LLC regarding the accuracy or completeness of the information. Ereztech LLC shall not be liable for any damages resulting from the handling, or from the contact with the above product.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Ereztech FE5291 Page 14 of 14 Revision: 1.11