EREZTECH LLC



11555 Medlock Bridge Road, Suite 100, Johns Creek, GA 30097, USA

T: +1.888.658.1221 F: 1.678.619.2020

E: info@ereztech.com W: https://ereztech.com

SAFETY DATA SHEET

Section 1. Identification

Product Name: <u>Aluminum chloride, anhydrous</u>

Product Type: Solid

CAS Number: 7446-70-0 Product Number: AL6700

Product Manufacturer: Ereztech LLC

11555 Medlock Bridge Road, Suite 100

Johns Creek, GA 30097

Product Information: (888) 658-1221

In Case of an Emergency: CHEMTREC: 1-800-424-9300 (USA);

+1 703-527-3887 (International); CCN836180
*** Contact manufacturer for all non-emergency calls.

Section 2. Hazards Identification

Appearance/Odor: Light yellow powder, pungent/strong chlorine odor.

Classification: CORROSIVE TO METALS - Category 1, H290

SKIN CORROSION/IRRITATION - Category 1B, H314

SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1, H318

HAZARDOUS TO THE AQUATIC ENVIRONMENT, ACUTE TOXICITY -

Category 3, H402

GHS Label Elements
Hazard Pictograms:



Signal Word: DANGER

Hazard Statements: H290: May be corrosive to metals.

H314: Causes severe skin burns and eye damage.

H318: Causes serious eye damage.

H402: Harmful to aquatic life.

Ereztech AL6700 Page 1 of 13 Revision: 1.20

Section 2. Hazards Identification

Precautionary statements

Prevention: P234: Keep only in original container.

P260: Do not breathe fumes/gases/mists/vapors or sprays.

P264: Wash skin thoroughly after handling. P273: Avoid release to the environment.

P280: Wear protective gloves/ protective clothing/ eye protection/

face protection.

Response: P301 + P330 + P331: IF SWALLOWED: Rinse mouth. Do NOT

induce vomiting.

P301 + P330 + P331: IF SWALLOWED: Rinse mouth. Do NOT

induce vomiting.

P303 + P361 + P353: If on skin (or hair): Take off immediately all

contaminated clothing. Rinse skin with water/shower.

P304 + P340: IF INHALED: Remove victim to fresh air and keep at

rest in a position comfortable for breathing.

P305 + P351 + P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present. Continue

rinsing.

P310: Immediately call a POISON CENTER or doctor/physician.

P363: Wash contaminated clothing before reuse. P390: Absorb spillage to prevent material damage.

P403 + P233 + P235: Store in a well ventilated place. Keep

container tightly closed. Keep cool.

P405: Store locked up.

P406: Store in corrosive resistant container with resistant inner

lining.

Disposal: P501: Dispose of contents/ container to an approved wasted

disposal plant.

General: None.

OSHA/HCS Status: This material is considered hazardous by the OSHA Hazard

Communication Standard (29 CFR 1910.1200).

Hazards Not Otherwise Classified (HNOC):

Reacts violently with water to release toxic/corrosive gases.

Section 3. Composition/Information on Ingredients

Substances

Storage:

Formula : AlCl₃

Molecular Weight : 133.34 g/mol CAS-No. : 7446-70-0

Synonyms : Aluminum trichloride

Ereztech AL6700 Page 2 of 13 Revision: 1.20

Section 3. Composition/Information on Ingredients

Ingredient Name	%	CAS Number
Aluminum chloride, anhydrous	>98	7446-70-0

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First Aid Measures

Description of Necessary First Aid Measures

General Advice: Move out of dangerous area. Call a POISON CENTER or doctor/physician

immediately. Show this safety data sheet to the doctor in attendance. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or

waistband.

Eye Contact: Immediately flush eyes with plenty of water, occasionally lifting the upper and

lower eyelids. Rinse for a minimum of 15 minutes. Check for and remove any contact lenses after initial rinse period and continue rinsing for an additional 15 minutes. Keep eyes wide open during rinsing process. Call a POISON CENTER

or doctor/physician immediately.

Skin Contact: Remove all contaminated clothing and shoes. Wash off contaminated skin with

soap and plenty of water. Call a POISON CENTER or doctor/physician

immediately.

Inhalation: Remove victim to fresh air and keep at rest in a position comfortable for

breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

Call a POISON CENTER or doctor/physician immediately.

Ingestion: Do NOT induce vomiting. Rinse mouth. Remove dentures if any. If vomiting

occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. Call a POISON CENTER

or doctor/physician immediately.

Most Important Symptoms/Effects, Acute and Delayed Potential Acute Health Effects

Eye Contact: Causes serious eye damage. Symptoms may include watering, redness, pain,

swelling of the eyelids, inability to keep eye open, blurred vison and

temporary/permanent loss of vision.

Inhalation: Product is extremely corrosive to mucous membranes and tissues of the upper

respiratory tract. Symptoms may include a burning sensation, coughing, coughing up blood (hemoptysis), wheezing, laryngitis, shortness of breath/difficulty in breathing (dyspnea), blueness (cyanosis) of lips and skin, nausea,

headaches, disorientation, general weakness and loss of consciousness.

Section 4. First Aid Measures

Skin Contact: Skin contact with this product may be expected to cause (severe) chemical

burns. Symptoms may include reddening of skin, a burning or itching sensation,

pain, blistering and tissue necrosis.

Ingestion: Ingestion may be expected to result in burns of the mouth and throat and

potential perforation of the esophagus and stomach. Symptoms may include pain when swallowing (odynophagia), difficulty swallowing (dysphagia), fever, nausea, recurrent vomiting (emesis) and vomiting of blood (hematemesis). Severe burns which may be accompanied by perforation of the esophagus and stomach may present additional symptoms of abdominal pain/rigidity, chest

and/or back pain.

Indication of Immediate Medical Attention and Special Treatment Needed, If Necessary

Notes to Physician: Treat symptomatically.

Specific Treatments: No specific treatment.

Protection of First Responders: No action taken shall be taken involving any personal risk

without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See Toxicological Information (Section 11)

Hazards:

Section 5. Fire Fighting Measures

General Hazards: Fire may produce irritating, corrosive and/or toxic gases.

Suitable Extinguishing Media: Use alcohol resistant foam, dry chemical or carbon dioxide

(CO₂).

Unsuitable Extinguishing Media: DO NOT USE WATER. Product reacts violently with water to

produce hydrogen chloride and hydrogen chloride gas.

be produced.

Product of Combustion: Decomposition products include aluminum oxides, hydrogen

chloride and hydrogen chloride gas.

Protection of Firefighters: Promptly isolate the scene by removing all persons from the

vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Fire-fighters should wear appropriate protection equipment and self-contained breathing apparatus (SCBA) with a full

face-piece operated in a positive pressure mode.

Section 6. Accidental Release Measures

Personal Precautions, Protective Equipment and Emergency Procedures

For Non-Emergency Personnel: No action shall be taken involving any personal risk or without

suitable training. Evacuate surrounding areas. Keep

unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid inhalation of dusts, vapors or fumes. Provide adequate ventilation. Wear respiratory protection. Put on appropriate personal protective

equipment.

For Emergency Responders: If specialized clothing is required to deal with the spillage, take

note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For Non-Emergency

Personnel".

Environmental Precautions: Do not allow dispersal of spilled material and contact with soil,

waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers,

waterways, soil or air).

Methods for Containment

General:

Spilled material will likely give off fumes and gases upon exposure to moisture in the air. Move containers from spill area if safe to do so. Avoid allowing the spilled material to get wet or using water to clean up spillages or residues.

Small Spill:

Contain and collect spillage with a dry, binding material (e.g. sand, earth, vermiculite or diatomaceous earth) and place in

dry, sealed container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal

contractor.

Large Spill: Approach release from upwind. Prevent entry into sewers,

water courses, basements or confined areas. Contain and collect spillage with a dry, binding material (e.g. sand, earth, vermiculite or diatomaceous earth) and place in dry, sealed container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal

contractor. Contaminated absorbent material may pose the

same hazard as the spilled product.

Note: see Section 1 for emergency contact information and

Section 13 for waste disposal.

Section 7. Handling and Storage

Precautions: Product is moisture sensitive; handle under a dry, inert gas.

Nitrogen with less than 5 ppm each of moisture and oxygen is recommended. Avoid formation and inhalation of dusts and aerosols. Keep container tightly sealed. Avoid contact with skin, eyes and clothing. Do not ingest. Avoid prolonged

exposure. Ensure adequate ventilation.

Protective Measures: Put on appropriate personal protective equipment (see Section

8). Keep in the original container kept tightly closed when not in use. Empty containers retain product residue and can be

hazardous. Do not reuse container.

General Occupational Hygiene: Eating, drinking and smoking should be prohibited in areas

where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective

equipment before entering eating areas. See also Section 8 for

additional information on hygiene measures.

Safe Storage Conditions: Product is moisture sensitive; store under an inert gas.

Nitrogen with less than 5 ppm each of moisture and oxygen is recommended. Store in original container protected from direct

sunlight in a dry and well-ventilated area, away from

incompatible materials and food and drink. Keep container tightly closed and sealed until ready for use. Store locked up.

Section 8. Exposure Controls/Personal Protection

Introductory Remarks:

These recommendations provide general guidance for handling this product. Because work environments and material handling practices vary, safety procedures should be developed for each intended application. While developing safe handling procedures, do not overlook the need to clean equipment and conduct regular repairs. Waste from these procedures should be handled in accordance with Section 13.

Occupational Exposure Limits

List	Components	CAS-No.	Туре	Value
ACGIH	Aluminum chloride	7446-70-0	TLV	2.0 mg/m ³ (Al metal) TWA

Engineering Controls:

Properly operating chemical fume hood designed for hazardous chemicals and having an average face velocity of at least 100 feet per minute. Provide an eyewash/shower station.

Section 8. Exposure Controls/Personal Protection

Environmental Exposure Controls:

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual Protection Measures

Hygiene Measures:

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Remove all soiled and contaminated clothing immediately. Do not inhale dusts/gases/fumes/vapors. Avoid contact with eyes and skin. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/Face Protection:

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to dust, vapors, or gases. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles, faceshield (8-inch minimum). Refer to 29 CFR 1910.133, ANSI Z87.1, or European Standard EN166.

Skin Protection

Hand Protection:

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: Chemical-resistant gloves.

Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product.

Section 8. Exposure Controls/Personal Protection

Hand Protection (cont.): Dispose of contaminated gloves after use in accordance with

applicable laws and good laboratory practices. Wash and dry hands. For full contact, wear gloves made from Neoprene or

nitrile rubber.

Other Skin Protection: Appropriate footwear and any additional skin protection

measures should be selected based on the task being

performed and the risks involved and should be approved by a

specialist before handling this product.

Respiratory Protection: Where risk assessment shows air-purifying respirators are

appropriate use a full-face respirator with multipurpose combination (US) or type ABEK (EN 14387) respirator

cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as

NIOSH (US) or CEN (EU).

Section 9. Physical and Chemical Properties

Physical State: Powder

Color: Light yellow

Odor: Pungent, strong chlorine odor

Odor Threshold: No data available.

pH: 2.4 (100 g/l aqueous solution).

Melting Point: 194 °C (381.2 °F).

Boiling Point: 187.7 °C (369.9 °F) at 1,003 hPa (752 mmHg).

Flash Point: Product is not flammable. **Relative Density:** 2.44 g/cm³ @ 20 °C.

Vapor Pressure:
No data available.
Vapor Density:
No data available.

Water Solubility: Product decomposes when exposed to water; will react

violently with water if water is added to product and will

produce toxic gases. Solubility: 450 g/l @ 20 °C.

Section 10. Stability and Reactivity

Reactivity: Product reacts violently if water is added to product.

Reaction will liberate toxic and corrosive gases (hydrogen

chloride).

Ereztech AL6700 Page 8 of 13 Revision: 1.20

Section 10. Stability and Reactivity

This product is stable when stored under a dry, inert **Chemical Stability:**

> atmosphere and away from heat. Nitrogen containing less than 5 ppm each moisture and air is recommended. This

product is not sensitive to impact.

Exposure to water/moisture. Conditions to Avoid:

Strong oxidizing agents, strong bases, alkali metals, **Incompatible Materials:**

metals, water/moisture.

Hazardous Decomposition Products: Under normal conditions of storage and use, hazardous

> decomposition products should not be produced. Hazardous decomposition products formed under fire conditions: aluminum oxides, hydrogen chloride and hydrogen chloride gas. In the event of a fire: see section

5.

Possibility of Hazardous Reactions:

Under normal conditions of storage and use, hazardous reactions will not occur. Hazardous reactions or instability may occur under certain conditions of storage or use.

Section 11. Toxicological Information

Information on Toxicological Effects

Acute Toxicity

Component	CAS No	Result	Species	Dose	Exposure
Aluminum chloride	7446-70-0	LD50 Oral	Rat	3,470 mg/kg	
- B R I D	GING	LD50 Dermal	Rat	> 2,000 mg/kg	-

Irritation/Corrosion

: Severe erythema/edema, skin rabbit and mouse, 10%, open exposure. Product produces chemical burns on skin, mucous membranes and eye tissues.

Sensitization Germ Cell Mutagenicity

Carcinogenity

IARC

: No specific data available. : No specific data available.

ACGIH

: No component of this product present at levels greater than 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

: No component of this product present at levels greater than 0.1% is identified as probable, possible or confirmed human carcinogen by ACGIH.

NTP

: No component of this product present at levels greater than 0.1% is identified as probable, possible or confirmed human carcinogen by NTP.

Section 11. Toxicological Information

OSHA

No component of this product present at levels greater than 0.1% is identified as probable, possible or confirmed human carcinogen by OSHA.

Reproductive Toxicity

: This product is not expected to cause reproductive or developmental effects.

Teratogenicity

: No specific data available.

Specific Target Organ Toxicity (Single Exposure)

: No specific data available.

Specific Target Organ Toxicity (Repeated Exposure)

: Respiratory system, skin.

Aspiration Hazard

: No specific data available.

Information on the Likely Routes of Exposure

: Common routes of exposure: inhalation (failure to prevent dust formation), dermal (failure to use skin protection), eye (failure to use safety eyewear). Less common: ingestion (failure to employ recommended hygiene measures (e.g. smoking after handling product without washing hands or using hand protection).

Additional Information

Prolonged or chronic exposure may cause irreversible damage to the lungs; symptoms may include bronchial irritation with chronic cough and frequent bouts of pneumonia. Gastrointestinal disturbances may also occur.

To the best of our knowledge, the chemical, physical and toxicological properties of this product have not been thoroughly investigated.

Section 12. Ecological Information

Numerical Measures of Toxicity

Component	CAS No	Test	Species	Dose	Exposure
Aluminum chloride	7446-70-0	LC50	Gambusia affinis	27.1 mg/l	97 h
		EC50	Daphnia magna (water flea)	3.9 mg/l	48 h

Persistence and Degradability

Biodegradability

Bioaccumulative Potential

Mobility in Soil

: No specific data available.

: No specific data available.

: No specific data available.

Section 12. Ecological Information

Other Adverse Effects

: Harmful to aquatic life. An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Section 13. Disposal Considerations

Waste Treatment Methods

Product Dispose of in accordance with local, state, and federal

regulations. Refer to 40 CFR 260-299 for complete waste

disposal regulations. Consult your local, state, or federal agency

before disposing of any chemicals.

Empty containers retain product residue (powder and/or vapors) **Contaminated Packaging**

and can be dangerous. Dispose of as unused product.

Section 14. Transport Information

	DOT	IMDG	IATA	
UN Number	UN 1726	UN 1726	UN 1726	
UN Proper Shipping Name	Aluminum chloride,	uminum chloride, ALUMINUM CHLORIDE,		
	anhydrous	ANHYDROUS	anhydrous	
Transport Hazard Classes	8	8	8	
Packing Group	II	II	II	
Environmental Hazards		<u>-</u>	-	
Additional Information	•	EMS No. F-A, S-B	-	

Special Precautions for User

: Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transporting in Bulk According to Annex II of MARPOL 73/78 and the IBC Code

: Not applicable.

Section 15. Regulatory Information

TSCA (Toxic Substance Control Act):

This product is listed on the U.S. Toxic Substances Control Act Chemical Inventory (TSCA Inventory).

SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

Ereztech AL6700 Page 11 of 13 Revision: 1.20

Section 15. Regulatory Information

SARA 313 Components

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

SARA 311/312 Hazards

Acute Health Hazard (Skin Corrosion or Irritation, Serious eye damage or eye irritation); HNOC: Releases corrosive/toxic gases when exposed to water.

Massachusetts Right to Know Components

	CAS-No.	Revision Date
Aluminum chloride, anhydrous	7446-70-0	1993-04-24
Pennsylvania Right to Know Components		
	CAS-No.	Revision Date
Aluminum chloride, anhydrous	7446-70-0	1993-04-24
New Jersey Right to Know Components		
	CAS-No.	Revision Date
Aluminum chloride, anhydrous	7446-70-0	1993-04-24

California Proposition 65 Components

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

Section 16. Other Information

National Fire Protection Association (U.S.A.)



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

Ereztech AL6700 Page 12 of 13 Revision: 1.20

Section 16. Other Information

HMIS Rating



History

Date of Printing : 4/19/2020

Date of Issue/Date of Revision : 4/19/2020

Date of Previous Issue : 1/29/2020

References : None available

Abbreviations and Acronyms

ACGIH: American Conference of Governmental Industrial Hygienists.

ATE: Acute Toxicity Estimate

CAS: Chemical Abstracts Service (division of the American Chemical Society).

DOT: US Department of Transportation.

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

HMIS: Hazardous Materials Identification System. IARC: International Agency for Research on Cancer.

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA).

IDLH: Immediately Dangerous to Life or Health (US National Institute for Occupation Health and Safety (NIOSH)).

IMDG: International Maritime Code for Dangerous Goods.

NFPA: National Fire Protection Association.

NIOSH: National Institute of Occupational Safety and Health.

NTP: National Toxicology Program.

OSHA: Occupational Safety and Health Administration.

PEL: Permissible Exposure Limits.
REL: Recommended Exposure Limits.

SARA: Superfund Amendments and Reauthorization Act.

STOT: Specific Target Organ Toxicity. TLV: Threshold Limit Values (ACGIH).

TWA: Time Weighted Average. VOC: Volatile Organic Compound.

Disclaimer

The information herein is believed to be accurate and is presented in good faith; however, no warranties or representations are made by Ereztech LLC regarding the accuracy or completeness of the information. Ereztech LLC shall not be liable for any damages resulting from the handling, or from the contact with the above product.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.