

SAFETY DATA SHEET

Version 5.2 Revision Date 09/23/2016 Print Date 11/14/2018

1. PRODUCT AND COMPANY IDENTIFICATION

1.1 Product identifiers

Product name : 5-MeO-DMT

Product Number : M-168
Brand : Cerilliant

CAS-No. : 1019-45-0

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

1.3 Details of the supplier of the safety data sheet

Company : Sigma-Aldrich

3050 Spruce Street SAINT LOUIS MO 63103

USA

Telephone : +1 800-325-5832 Fax : +1 800-325-5052

1.4 Emergency telephone number

Emergency Phone # : +1-703-527-3887 (CHEMTREC)

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Flammable liquids (Category 2), H225 Acute toxicity, Oral (Category 3), H301 Acute toxicity, Inhalation (Category 3), H331 Acute toxicity, Dermal (Category 3), H311

Specific target organ toxicity - single exposure (Category 1), H370

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

Pictogram



Signal word Danger

Hazard statement(s)

H225 Highly flammable liquid and vapour.

H301 + H311 + H331 Toxic if swallowed, in contact with skin or if inhaled

H370 Causes damage to organs.

Precautionary statement(s)

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.

P242 Use only non-sparking tools.

Cerilliant - M-168 Page 1 of 9

P260 P264 P270 P270 P270 P270 Do not eat, drink or smoke when using this product. P271 P280 P280 P301 + P310 + P330 P303 + P361 + P353 P304 + P340 + P311 P363 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray. Wash skin thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves/ eye protection/ face protection. IF SWALLOWED: Immediately call a POISON CENTER/doctor. Rinse mouth. IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician. P307 + P311 P363 Wash contaminated clothing before reuse	P243	Take precautionary measures against static discharge.
P270 Do not eat, drink or smoke when using this product. P271 Use only outdoors or in a well-ventilated area. P280 Wear protective gloves/ eye protection/ face protection. P301 + P310 + P330 IF SWALLOWED: Immediately call a POISON CENTER/doctor. Rinse mouth. P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower. P304 + P340 + P311 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician. P307 + P311 IF exposed: Call a POISON CENTER or doctor/ physician.	P260	Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
P271 Use only outdoors or in a well-ventilated area. P280 Wear protective gloves/ eye protection/ face protection. P301 + P310 + P330 IF SWALLOWED: Immediately call a POISON CENTER/doctor. Rinse mouth. P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower. P304 + P340 + P311 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician. P307 + P311 IF exposed: Call a POISON CENTER or doctor/ physician.	P264	Wash skin thoroughly after handling.
P280 Wear protective gloves/ eye protection/ face protection. P301 + P310 + P330 IF SWALLOWED: Immediately call a POISON CENTER/doctor. Rinse mouth. P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower. P304 + P340 + P311 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician. P307 + P311 IF exposed: Call a POISON CENTER or doctor/ physician.	P270	Do not eat, drink or smoke when using this product.
P301 + P310 + P330 IF SWALLOWED: Immediately call a POISON CENTER/doctor. Rinse mouth. P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower. P304 + P340 + P311 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician. P307 + P311 IF exposed: Call a POISON CENTER or doctor/ physician.	P271	Use only outdoors or in a well-ventilated area.
mouth. P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower. P304 + P340 + P311 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician. P307 + P311 IF exposed: Call a POISON CENTER or doctor/ physician.	P280	Wear protective gloves/ eye protection/ face protection.
clothing. Rinse skin with water/ shower. P304 + P340 + P311 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician. P307 + P311 IF exposed: Call a POISON CENTER or doctor/ physician.	P301 + P310 + P330	
comfortable for breathing. Call a POISON CENTER or doctor/ physician. P307 + P311 IF exposed: Call a POISON CENTER or doctor/ physician.	P303 + P361 + P353	
	P304 + P340 + P311	
P363 Wash contaminated clothing before reuse	P307 + P311	IF exposed: Call a POISON CENTER or doctor/ physician.
Wash contaminated dotting before rease.	P363	Wash contaminated clothing before reuse.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.	P370 + P378	· · · · · · · · · · · · · · · · · · ·
P403 + P233 Store in a well-ventilated place. Keep container tightly closed.	P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P403 + P235 Store in a well-ventilated place. Keep cool. P405 Store locked up.		·
P501 Dispose of contents/ container to an approved waste disposal plant.	P501	•

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

3. COMPOSITION/INFORMATION ON INGREDIENTS

3.2 Mixtures

Molecular weight : 32.04 g/mol

Hazardous components

Component		Classification	Concentration
Methanol			
CAS-No.	67-56-1	Flam. Liq. 2; Acute Tox. 3;	>= 90 - <= 100
EC-No.	200-659-6	STOT SE 1; H225, H301 +	%
Index-No.	603-001-00-X	H311 + H331, H370	
Registration number	01-2119433307-44-XXXX		

For the full text of the H-Statements mentioned in this Section, see Section 16.

4. FIRST AID MEASURES

4.1 Description of first aid measures

General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Wash off with soap and plenty of water. Take victim immediately to hospital. Consult a physician.

In case of eye contact

Flush eyes with water as a precaution.

If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

Cerilliant - M-168 Page 2 of 9

5. FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2 Special hazards arising from the substance or mixture

No data available

5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

5.4 Further information

Use water spray to cool unopened containers.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Wear respiratory protection. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

For personal protection see section 8.

6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

6.3 Methods and materials for containment and cleaning up

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13).

6.4 Reference to other sections

For disposal see section 13.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist.

Use explosion-proof equipment. Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge.

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Recommended storage temperature -20 °C

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Components with workplace control parameters

Component	CAS-No.	Value	Control parameters	Basis	
Methanol	67-56-1	TWA	200.000000 ppm	USA. ACGIH Threshold Limit Values (TLV)	
	Remarks	Headache Nausea Dizziness Eye damage Substances for which there is a Biological Exposure Index or Indices			

Cerilliant - M-168 Page 3 of 9

(see BEI® s	section)		
Danger of cutaneous absorption			
STEL	250.000000 ppm	USA. ACGIH Threshold Limit Values (TLV)	
Headache Nausea Dizziness Eye damage Substances (see BEI® s	for which there is	s a Biological Exposure Index or Indices	
	utaneous absorpt	ion	
TWA	200.000000 ppm 260.000000 mg/m3	USA. NIOSH Recommended Exposure Limits	
Potential for	dermal absorptio	nn	
ST	250.000000 ppm 325.000000 mg/m3	USA. NIOSH Recommended Exposure Limits	
Potential for	dermal absorption	on	
TWA	200.000000 ppm 260.000000 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants	
The value in	n mg/m3 is approx	kimate.	
TWA	200 ppm	USA. ACGIH Threshold Limit Values (TLV)	
Headache Nausea Dizziness			
(see BEI® s	for which there is ection)	a Biological Exposure Index or Indices	
Substances (see BEI® s	for which there is		
Substances (see BEI® s Danger of c STEL Headache Nausea Dizziness Eye damage Substances (see BEI® s	for which there is section) utaneous absorpt 250 ppm e for which there is section)	ion USA. ACGIH Threshold Limit Values (TLV) s a Biological Exposure Index or Indices	
Substances (see BEI® s Danger of c STEL Headache Nausea Dizziness Eye damage Substances (see BEI® s	for which there is section) utaneous absorpt 250 ppm e for which there is section) utaneous absorpt 200 ppm	ion USA. ACGIH Threshold Limit Values (TLV) s a Biological Exposure Index or Indices ion USA. NIOSH Recommended	
Substances (see BEI® s Danger of c STEL Headache Nausea Dizziness Eye damage Substances (see BEI® s Danger of c TWA	for which there is section) utaneous absorpt 250 ppm e for which there is section) utaneous absorpt 200 ppm 260 mg/m3	ion USA. ACGIH Threshold Limit Values (TLV) s a Biological Exposure Index or Indices ion USA. NIOSH Recommended Exposure Limits	
Substances (see BEI® s Danger of c STEL Headache Nausea Dizziness Eye damage Substances (see BEI® s Danger of c TWA	for which there is section) utaneous absorpt 250 ppm e for which there is section) utaneous absorpt 200 ppm 260 mg/m3 dermal absorption 250 ppm	ion USA. ACGIH Threshold Limit Values (TLV) s a Biological Exposure Index or Indices ion USA. NIOSH Recommended Exposure Limits	
Substances (see BEI® s Danger of construction STEL Headache Nausea Dizziness Eye damage Substances (see BEI® s Danger of construction TWA Potential for	for which there is section) utaneous absorpt 250 ppm e for which there is section) utaneous absorpt utaneous absorpt 200 ppm 260 mg/m3	ion USA. ACGIH Threshold Limit Values (TLV) a a Biological Exposure Index or Indices ion USA. NIOSH Recommended Exposure Limits USA. NIOSH Recommended Exposure Limits	
Substances (see BEI® s Danger of ci STEL Headache Nausea Dizziness Eye damage Substances (see BEI® s Danger of ci TWA Potential for ST Potential for TWA	for which there is section) utaneous absorpt 250 ppm effor which there is section) utaneous absorpt 200 ppm 260 mg/m3 dermal absorption 250 ppm 325 mg/m3 dermal absorption 200 ppm 260 mg/m3	USA. ACGIH Threshold Limit Values (TLV) a a Biological Exposure Index or Indices ion USA. NIOSH Recommended Exposure Limits USA. NIOSH Recommended Exposure Limits USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants	
Substances (see BEI® s Danger of colors STEL Headache Nausea Dizziness Eye damage Substances (see BEI® s Danger of colors TWA Potential for ST Potential for TWA The value in	for which there is section) utaneous absorpt 250 ppm for which there is section) utaneous absorpt 200 ppm 260 mg/m3 dermal absorptic 250 ppm 325 mg/m3 dermal absorptic 200 ppm 260 mg/m3	ion USA. ACGIH Threshold Limit Values (TLV) a a Biological Exposure Index or Indices ion USA. NIOSH Recommended Exposure Limits on USA. NIOSH Recommended Exposure Limits on USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants cimate.	
Substances (see BEI® s Danger of ci STEL Headache Nausea Dizziness Eye damage Substances (see BEI® s Danger of ci TWA Potential for ST Potential for TWA	for which there is section) utaneous absorpt 250 ppm 250 ppm for which there is section) utaneous absorpt 200 ppm 260 mg/m3 dermal absorption 250 ppm 325 mg/m3 dermal absorption 260 mg/m3 dermal absorption 250 ppm 260 mg/m3 dermal absorption 250 ppm 250 ppm 325 mg/m3	USA. ACGIH Threshold Limit Values (TLV) a a Biological Exposure Index or Indices ion USA. NIOSH Recommended Exposure Limits USA. NIOSH Recommended Exposure Limits USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants	

Cerilliant - M-168 Page 4 of 9

TWA	200 ppm 260 mg/m3	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000		
Skin nota	Skin notation			
С	1,000 ppm	California permissible exposure limits for chemical contaminants (Title 8, Article 107)		
Skin	Skin			
PEL	200 ppm 260 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)		
Skin	Skin			
STEL	250 ppm 325 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)		
Skin		·		

Biological occupational exposure limits

Biological occupational exposure mints					
Component	CAS-No.	Parameters	Value	Biological specimen	Basis
Methanol	67-56-1	Methanol	15.0000 mg/l	Urine	ACGIH - Biological Exposure Indices (BEI)
	Remarks	End of shift (A	End of shift (As soon as possible after exposure ceases)		
		Methanol	15 mg/l	Urine	ACGIH - Biological Exposure Indices (BEI)
		End of shift (As soon as possible after exposure ceases)			

8.2 Exposure controls

Appropriate engineering controls

Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product.

Personal protective equipment

Eye/face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Body Protection

Complete suit protecting against chemicals, Flame retardant antistatic protective clothing., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type AXBEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

a) Appearance Form: liquid Colour: colourless

Cerilliant - M-168 Page 5 of 9

Odour b) pungent

Odour Threshold No data available d) No data available

Melting point/freezing

Melting point/range: -97.99 °C (-144.38 °F)

Initial boiling point and

boiling range

64.0 - 65.0 °C (147.2 - 149.0 °F) at 1,013 hPa (760 mmHg)

9.7 °C (49.5 °F) - closed cup g) Flash point

h) Evaporation rate No data available No data available i) Flammability (solid, gas)

Upper/lower Upper explosion limit: 36 %(V) flammability or Lower explosion limit: 6 %(V)

explosive limits

k) Vapour pressure 130.3 hPa (97.7 mmHg) at 20.0 °C (68.0 °F)

> 546.6 hPa (410.0 mmHg) at 50.0 °C (122.0 °F) 169.27 hPa (126.96 mmHg) at 25.0 °C (77.0 °F)

Vapour density 1.11

0.79 g/cm3 at 20 °C (68 °F) m) Relative density

n) Water solubility completely miscible Partition coefficient: nlog Pow: -0.769

octanol/water

455.0 °C (851.0 °F) at 1,013 hPa (760 mmHg)

Auto-ignition temperature

Decomposition temperature

No data available

No data available Viscosity

s) Explosive properties Not explosive

Oxidizing properties The substance or mixture is not classified as oxidizing.

9.2 Other safety information

> Minimum ignition energy 0.14 mJ Conductivity < 1 µS/cm

Relative vapour density 1.11

10. STABILITY AND REACTIVITY

10.1 Reactivity

No data available

10.2 Chemical stability

Stable under recommended storage conditions. Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Vapours may form explosive mixture with air. Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Heat, flames and sparks.

Heat, flames and sparks.

10.5 Incompatible materials

Acid chlorides, Acid anhydrides, Oxidizing agents, Alkali metals, Reducing agents, Acids

Cerilliant - M-168 Page 6 of 9

10.6 Hazardous decomposition products

Hazardous decomposition products formed under fire conditions. - Carbon oxides In the event of fire: see section 5

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity

No data available

Inhalation: No data available Dermal: No data available

No data available

Skin corrosion/irritation

No data available

Serious eye damage/eye irritation

No data available

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as

probable, possible or confirmed human carcinogen by IARC.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a

carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a

known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a

carcinogen or potential carcinogen by OSHA.

Reproductive toxicity

No data available No data available

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

Additional Information

RTECS: Not available

Methyl alcohol may be fatal or cause blindness if swallowed.

Effects due to ingestion may include:, Headache, Dizziness, Drowsiness, metabolic acidosis, Coma, Seizures.

Symptoms may be delayed., Damage of the:, Liver, Kidney

Stomach - Irregularities - Based on Human Evidence

Stomach - Irregularities - Based on Human Evidence

Stomach - Irregularities - Based on Human Evidence (5-Methoxy-N,N-dimethyl-1H-indole-3-ethylamine)

Cerilliant - M-168 Page 7 of 9

12. ECOLOGICAL INFORMATION

12.1 Toxicity

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Other adverse effects

No data available

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Product

Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

Contaminated packaging

Dispose of as unused product.

14. TRANSPORT INFORMATION

DOT (US)

UN number: 1230 Class: 3 Packing group: II

Proper shipping name: Methanol, solution

Reportable Quantity (RQ):

Poison Inhalation Hazard: No

IMDG

UN number: 1230 Class: 3 (6.1) Packing group: II EMS-No: F-E, S-D

Proper shipping name: METHANOL, SOLUTION

IATA

UN number: 1230 Class: 3 (6.1) Packing group: II

Proper shipping name: Methanol, solution

15. REGULATORY INFORMATION

SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Components

The following components are subject to reporting levels established by SARA Title III, Section 313:

CAS-No. Revision Date 67-56-1 2007-07-01

Methanol 67-56-1 2007-07-01

SARA 311/312 Hazards

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

Massachusetts Right To Know Components

 Methanol
 CAS-No.
 Revision Date

 47-56-1
 2007-07-01

Pennsylvania Right To Know Components

Cerilliant - M-168 Page 8 of 9

CAS-No. Revision Date Methanol 67-56-1 2007-07-01

New Jersey Right To Know Components

 Methanol
 CAS-No.
 Revision Date

 47-56-1
 2007-07-01

California Prop. 65 Components

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive 67-56-1 Revision Date 2012-03-16

harm. Methanol

16. OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3.

Acute Tox. Acute toxicity
Flam. Liq. Flammable liquids

H225 Highly flammable liquid and vapour.

H301 Toxic if swallowed.

H301 + H311 + Toxic if swallowed, in contact with skin or if inhaled

H331

H311 Toxic in contact with skin.

H331 Toxic if inhaled.

H370 Causes damage to organs.

STOT SE Specific target organ toxicity - single exposure

HMIS Rating

Health hazard: 2
Chronic Health Hazard: *
Flammability: 3
Physical Hazard 0

NFPA Rating

Health hazard: 2
Fire Hazard: 3
Reactivity Hazard: 0

Further information

Copyright 2016 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Preparation Information

Sigma-Aldrich Corporation Product Safety – Americas Region 1-800-521-8956

Version: 5.2 Revision Date: 09/23/2016 Print Date: 11/14/2018

Cerilliant - M-168 Page 9 of 9