SAFETY DATA SHEET

Version 3.13 Revision Date 09/23/2016 Print Date 11/02/2018

1. PRODUCT AND COMPANY IDENTIFICATION

1.1 Product identifiers

Product name : N-(1-Naphthyl)ethylenediamine dihydrochloride

monomethanolate

Product Number : 70720

Brand : Sigma-Aldrich

CAS-No. : 1357471-44-3

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

1.3 Details of the supplier of the safety data sheet

Company : Sigma-Aldrich

3050 Spruce Street SAINT LOUIS MO 63103

USA

Telephone : +1 800-325-5832 Fax : +1 800-325-5052

1.4 Emergency telephone number

Emergency Phone # : +1-703-527-3887 (CHEMTREC)

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Acute toxicity, Oral (Category 4), H302 Skin irritation (Category 2), H315 Eye irritation (Category 2A), H319

Specific target organ toxicity - single exposure (Category 1), H370

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

Pictogram



Signal word Danger

Hazard statement(s)

H302 Harmful if swallowed. H315 Causes skin irritation.

H319 Causes serious eye irritation. H370 Causes damage to organs.

Precautionary statement(s)

P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.
P280 Wear protective gloves/ eye protection/ face protection.

Sigma-Aldrich - 70720 Page 1 of 9

P301 + P312 + P330 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell. Rinse mouth. P302 + P352 IF ON SKIN: Wash with plenty of soap and water. IF IN EYES: Rinse cautiously with water for several minutes. Remove P305 + P351 + P338 contact lenses, if present and easy to do. Continue rinsing. IF exposed: Call a POISON CENTER or doctor/ physician. P307 + P311 P332 + P313 If skin irritation occurs: Get medical advice/ attention. P337 + P313 If eye irritation persists: Get medical advice/ attention. P362 Take off contaminated clothing and wash before reuse. P405 Store locked up. P501 Dispose of contents/ container to an approved waste disposal plant.

Hazards not otherwise classified (HNOC) or not covered by GHS - none

` ,

3.2 Mixtures

2.3

Formula : C12H14N2 · 2HCI · CH4O

Molecular weight : 291.22 g/mol

3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous components

Component		Classification	Concentration		
N-2-Aminoethyl-1-naphthylamine dihydrochloride					
CAS-No. EC-No.	1465-25-4 215-981-2	Skin Irrit. 2; Eye Irrit. 2A; H315, H319	>= 70 - < 90 %		
Methanol					
CAS-No.	67-56-1	Flam. Liq. 2; Acute Tox. 3;	>= 10 - < 20 %		
EC-No.	200-659-6	STOT SE 1; H225, H301 +			
Index-No.	603-001-00-X	H311 + H331, H370			
Registration number	01-2119433307-44-XXXX				

For the full text of the H-Statements mentioned in this Section, see Section 16.

4. FIRST AID MEASURES

4.1 Description of first aid measures

General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Wash off with soap and plenty of water. Take victim immediately to hospital. Consult a physician.

In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

If swallowed

Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

5. FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Sigma-Aldrich - 70720 Page 2 of 9

5.2 Special hazards arising from the substance or mixture

No data available

5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

5.4 Further information

No data available

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Avoid dust formation. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Evacuate personnel to safe areas. Avoid breathing dust.

For personal protection see section 8.

6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

6.3 Methods and materials for containment and cleaning up

Pick up and arrange disposal without creating dust. Sweep up and shovel. Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For disposal see section 13.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid formation of dust and aerosols. Further processing of solid materials may result in the formation of combustible dusts. The potential for combustible dust formation should be taken into consideration before additional processing occurs.

Provide appropriate exhaust ventilation at places where dust is formed.

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place.

Hygroscopic. Light sensitive. Store under inert gas. Air sensitive.

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Components with workplace control parameters

Component	CAS-No.	Value	Control parameters	Basis	
Methanol	67-56-1	TWA	200.000000 ppm	USA. ACGIH Threshold Limit Values (TLV)	
	Remarks	Headache Nausea Dizziness Eye damage Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Danger of cutaneous absorption			
		STEL	250.000000 ppm	USA. ACGIH Threshold Limit Values (TLV)	
		Headache Nausea Dizziness			

Sigma-Aldrich - 70720 Page 3 of 9

Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Danger of cutaneous absorption TWA 200.000000 USA. NIOSH Recommended Exposure Limits 280.000000 USA. DIOSH Recommended Exposure Limits 280.00000 USA. DIOSH Recommended Exposure Limits 280.00000 USA. DIOSH Recommended Exposure Limits 280.000000 USA. DIOSH Recommended 280.000000 USA. DIOSH DI	I I	Eye damage			
(see BEI® section) Danger of cutaneous absorption TWA 200.000000 USA. NIOSH Recommended Exposure Limits 280.000000 mg/m3 280.000000 USA. NIOSH Recommended Exposure Limits 280.000000 mg/m3 280.000000 USA. Occupational Exposure Limits Contaminants 180.000000 USA. Occupational Exposure Limits 180.0000000 USA. Occupational Exposure Limits 180.0000000 USA. Occupational Exposure Limits 180.0000000 USA. Occupational Exposure Limits 180.00000000 USA. Occupational Exposure Limits 180.00000000000000000000000000000000000					
TWA 200.00000 ppm 260.00000 ppm 260.000000 ppm 260.000000 mg/m3 Potential for dermal absorption ST 250.000000 ppm ppm 250.000000 ppm 250.000000 ppm 250.000000 ppm 260.000000 ppm 260.0000000 ppm 260.0000000 ppm 260.0000000 ppm 260.00000000000000000000000000000000000					
ppm 260,000000 mg/m3 Potential for dermal absorption ST 250,000000 mg/m3 Exposure Limits ST 250,000000 mg/m3 Potential for dermal absorption USA, NIOSH Recommended Exposure Limits ST 250,00000 mg/m3 Potential for dermal absorption USA, Occupational Exposure Limits COSHA) - Table Z-1 Limits for Air COntaminants COSHA) - Table Z-1 Limits for Air					
260.00000 mg/m3 Potential for dermal absorption		TWA	200.000000		
Potential for dermal absorption ST Z50.000000 DPM Exposure Limits S25.000000 DPM Exposure Limits S25.000000 DPM Exposure Limits S25.000000 DPM				Exposure Limits	
Potential for dermal absorption ST 250.000000 DSA. NIOSH Recommended Exposure Limits Exposure					
ST		Determination			
ppm 325.000000 mg/m3 Potential for dermal absorption TWA 200 ppm 280.000000 USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants The value in mg/m3 is approximate. TWA 200 ppm USA. ACGIH Threshold Limit Values (TLV) Headache Nausea Dizziness Eye damage Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Danger of cutaneous absorption STEL 250 ppm USA. ACGIH Threshold Limit Values (TLV) Headache Nausea Dizziness Eye damage Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Danger of cutaneous absorption TWA 250 ppm USA. NIOSH Recommended (see BEI® section) Danger of cutaneous absorption TWA 200 ppm USA. NIOSH Recommended Exposure Limits Potential for dermal absorption ST 250 ppm USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 200 ppm USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 200 ppm USA. Occupational Exposure Limits Potential for dermal absorption TWA 200 ppm USA. Occupational Exposure Limits Potential for dermal absorption TWA 200 ppm USA. Occupational Exposure Limits Potential for dermal absorption TWA 200 ppm USA. OsHA - TABLE Z-1 Limits for Air Contaminants The value in mg/m3 is approximate. STEL 250 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants The value in mg/m3 is approximate. STEL 250 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 Skin notation TWA 200 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 Skin notation C 1,000 ppm California permissible exposure limits for chemical contaminants					
S25,00000 mg/m3 Potential for dermal absorption TWA 200,00000 contaminants Twantaminants Twantamin		31			
Mg/m3 Potential for dermal absorption TWA 200,000000				Exposure Elimits	
Potential for dermal absorption TWA 200.00000 USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air 260.00000 mg/m3 The value in mg/m3 is approximate. TWA 200 ppm USA. ACGIH Threshold Limit Values (TLV) Headache Nausea Dizziness Eye damage Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Danger of cutaneous absorption STEL 250 ppm USA. ACGIH Threshold Limit Values (TLV) Headache Nausea Dizziness Eye damage Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Danger of cutaneous absorption USA. ACGIH Threshold Limit Values (TLV) Headache Nausea Dizziness Eye damage Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Danger of cutaneous absorption USA. NIOSH Recommended Exposure Limits Exposure L					
TWA 200,000000 USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air 260,000000 mg/m3 The value in mg/m3 is approximate. The value in mg/m3 is approximate. TWA 200 ppm USA. ACGIH Threshold Limit Values (TLV) Headache Nausea Dizziness Eye damage Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Danger of cutaneous absorption STEL 250 ppm USA. ACGIH Threshold Limit Values (TLV) Headache Nausea Dizziness Eye damage Substances for which there is a Biological Exposure Index or Indices (see BEI® section) USA Danger of cutaneous absorption TWA 200 ppm USA. NIOSH Recommended USA Danger of cutaneous absorption TWA 200 ppm USA. NIOSH Recommended USA Danger of cutaneous absorption USA Danger of cutaneous absorption TWA 200 ppm USA Danger USA Danger					
ppm 260,00000 CostA) - Table Z-1 Limits for Air 260,00000 The value in mg/m3 is approximate. The value in mg/m3 is approximate. TWA 200 ppm USA. ACGIH Threshold Limit Values (TLV) Headache Nausea Dizziness Eye damage Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Danger of cutaneous absorption STEL 250 ppm USA. ACGIH Threshold Limit Values (TLV) Headache Nausea Dizziness Eye damage Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Danger of cutaneous absorption TWA 200 ppm USA. NIOSH Recommended Exposure Limits Potential for dermal absorption ST 250 ppm USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 200 ppm USA. OSHA - Table Z-1 Limits for Air Contaminants The value in mg/m3 is approximate. STEL 250 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants The value in mg/m3 is approximate. STEL 250 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 Skin notation TWA 200 ppm USA. OSHA - TABLE Z-1 Limits for 260 mg/m3 Air Contaminants - 1910.1000 Skin notation C 1,000 ppm USA. OSHA - TABLE Z-1 Limits for 260 mg/m3 Air Contaminants - 1910.1000 Skin notation C 1,000 ppm USA. Osha - Table Exposure limits for chemical contaminants (Title 8, Article 107)					
mg/m3			ppm		
The value in mg/m3 is approximate. TWA 200 ppm USA. ACGIH Threshold Limit Values (TLV) Headache Nausea Dizziness Eye damage Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Danger of cutaneous absorption STEL 250 ppm USA. ACGIH Threshold Limit Values (TLV) Headache Nausea Dizziness Eye damage Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Danger of cutaneous absorption TWA 200 ppm USA. NIOSH Recommended Exposure Limits Potential for dermal absorption ST 250 ppm USA. NIOSH Recommended Exposure Limits Potential for dermal absorption ST 250 ppm USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 200 ppm USA. NIOSH Recommended Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants The value in mg/m3 is approximate. The value in mg/m3 is approximate. STEL 250 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 Skin notation TWA 200 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 Skin notation TWA 200 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 Skin notation C 1,000 ppm California permissible exposure limits for chemical contaminants (Title 8, Article 107)			260.000000	Contaminants	
TWA					
Headache Nausea Dizziness Eye damage Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Danger of cutaneous absorption STEL 250 ppm USA. ACGIH Threshold Limit Values (TLV) Headache Nausea Dizziness Eye damage Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Danger of cutaneous absorption TWA 200 ppm USA. NIOSH Recommended Exposure Limits Potential for dermal absorption ST 250 ppm USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 200 ppm USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 200 ppm USA. Occupational Exposure Limits Contaminants The value in mg/m3 is approximate. The value in mg/m3 is approximate. STEL 250 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 Skin notation TWA 200 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 Skin notation C 1,000 ppm California permissible exposure limits for chemical contaminants (Title 8, Article 107)		•			
Nausea Dizziness Eye damage Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Danger of cutaneous absorption STEL 250 ppm USA. ACGIH Threshold Limit Values (TLV) Headache Nausea Dizziness Eye damage Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Danger of cutaneous absorption TWA 200 ppm USA. NIOSH Recommended Exposure Limits Potential for dermal absorption ST 250 ppm USA. NIOSH Recommended Exposure Limits Potential for dermal absorption ST 250 ppm USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 200 ppm USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 200 ppm USA. Occupational Exposure Limits Contaminants The value in mg/m3 is approximate. STEL 250 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 Skin notation TWA 200 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 Skin notation C 1,000 ppm California permissible exposure limits for chemical contaminants Citite 8, Article 107)			200 ppm		
Dizziness Eye damage Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Danger of cutaneous absorption STEL 250 ppm USA. ACGIH Threshold Limit Values (TLV) Headache Nausea Dizziness Eye damage Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Danger of cutaneous absorption TWA 200 ppm USA. NIOSH Recommended Exposure Limits Potential for dermal absorption ST 250 ppm USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 200 ppm USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 200 ppm USA. Occupational Exposure Limits Potential for dermal absorption TWA 200 ppm USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants The value in mg/m3 is approximate. STEL 250 ppm USA. OSHA - TABLE Z-1 Limits for 325 mg/m3 Air Contaminants - 1910.1000 Skin notation TWA 200 ppm USA. OSHA - TABLE Z-1 Limits for 260 mg/m3 Air Contaminants - 1910.1000 Skin notation C 1,000 ppm California permissible exposure limits for chemical contaminants (Title 8, Article 107)					
Eye damage Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Danger of cutaneous absorption STEL 250 ppm USA. ACGIH Threshold Limit Values (TLV) Headache Nausea Dizziness Eye damage Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Danger of cutaneous absorption TWA 200 ppm USA. NIOSH Recommended Exposure Limits Potential for dermal absorption ST 250 ppm USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 200 ppm USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 200 ppm USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 200 ppm USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants The value in mg/m3 is approximate. STEL 250 ppm USA. OSHA - TABLE Z-1 Limits for 325 mg/m3 Air Contaminants - 1910.1000 Skin notation TWA 200 ppm USA. OSHA - TABLE Z-1 Limits for 260 mg/m3 Air Contaminants - 1910.1000 Skin notation C 1,000 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 Skin notation C 1,000 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000					
Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Danger of cutaneous absorption STEL 250 ppm USA. ACGIH Threshold Limit Values (TLV) Headache Nausea Dizziness Eye damage Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Danger of cutaneous absorption TWA 200 ppm USA. NIOSH Recommended 260 mg/m3 Exposure Limits Potential for dermal absorption ST 250 ppm USA. NIOSH Recommended 325 mg/m3 Exposure Limits Potential for dermal absorption TWA 200 ppm USA. NIOSH Recommended 325 mg/m3 Exposure Limits Potential for dermal absorption TWA 200 ppm USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air (Contaminants The value in mg/m3 is approximate. STEL 250 ppm USA. OSHA - TABLE Z-1 Limits for 325 mg/m3 Air Contaminants - 1910.1000 Skin notation TWA 200 ppm USA. OSHA - TABLE Z-1 Limits for 260 mg/m3 Air Contaminants - 1910.1000 Skin notation C 1,000 ppm California permissible exposure limits for chemical contaminants (Title 8, Article 107)					
(see BEI® section) Danger of cutaneous absorption STEL 250 ppm USA. ACGIH Threshold Limit Values (TLV) Headache Nausea Dizziness Eye damage Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Danger of cutaneous absorption TWA 200 ppm USA. NIOSH Recommended Exposure Limits Potential for dermal absorption ST 250 ppm USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 200 ppm USA. NIOSH Recommended (OSHA) - Table Z-1 Limits for Air Contaminants The value in mg/m3 is approximate. STEL 250 ppm USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants The value in mg/m3 is approximate. STEL 250 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 Skin notation TWA 200 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 Skin notation C 1,000 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 Skin notation C 260 mg/m3 Air Contaminants - 1910.1000					
Danger of cutaneous absorption STEL 250 ppm USA. ACGIH Threshold Limit Values (TLV) Headache Nausea Dizziness Eye damage Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Danger of cutaneous absorption TWA 200 ppm USA. NIOSH Recommended Exposure Limits Expo					
STEL 250 ppm USA. ACGIH Threshold Limit Values (TLV) Headache Nausea Dizziness Eye damage Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Danger of cutaneous absorption TWA 200 ppm USA. NIOSH Recommended Exposure Limits Potential for dermal absorption ST 250 ppm USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 200 ppm USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 200 ppm USA. Occupational Exposure Limits COSHA) - Table Z-1 Limits for Air Contaminants The value in mg/m3 is approximate. STEL 250 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 Skin notation TWA 200 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 Skin notation C 1,000 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 Skin notation C 1,000 ppm California permissible exposure limits for chemical contaminants (Title 8, Article 107)					
Headache Nausea Dizziness Eye damage Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Danger of cutaneous absorption TWA 200 ppm USA. NIOSH Recommended Exposure Limits Potential for dermal absorption ST 250 ppm USA. NIOSH Recommended Exposure Limits Potential for dermal absorption ST 250 ppm USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 200 ppm USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants The value in mg/m3 is approximate. STEL 250 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 Skin notation TWA 200 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 Skin notation TWA 200 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 Skin notation C 1,000 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 Skin notation C 1,000 ppm California permissible exposure California permissible ex					
Nausea Dizziness Eye damage Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Danger of cutaneous absorption TWA 200 ppm USA. NIOSH Recommended Exposure Limits Potential for dermal absorption ST 250 ppm USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 200 ppm USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 200 ppm USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants The value in mg/m3 is approximate. STEL 250 ppm USA. OSHA - TABLE Z-1 Limits for 325 mg/m3 Air Contaminants - 1910.1000 Skin notation TWA 200 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 Skin notation C 1,000 ppm California permissible exposure limits for chemical contaminants (Title 8, Article 107)				(TLV)	
Dizziness Eye damage Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Danger of cutaneous absorption TWA 200 ppm USA. NIOSH Recommended Exposure Limits Potential for dermal absorption ST 250 ppm USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 200 ppm USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 200 ppm USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants The value in mg/m3 is approximate. STEL 250 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 Skin notation TWA 200 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 Skin notation TWA 200 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 Skin notation C 1,000 ppm California permissible exposure limits for chemical contaminants (Title 8, Article 107)					
Eye damage Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Danger of cutaneous absorption TWA 200 ppm USA. NIOSH Recommended 260 mg/m3 Exposure Limits Potential for dermal absorption ST 250 ppm USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 200 ppm USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 200 ppm USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air (Contaminants The value in mg/m3 is approximate. STEL 250 ppm USA. OSHA - TABLE Z-1 Limits for 325 mg/m3 Air Contaminants - 1910.1000 Skin notation TWA 200 ppm USA. OSHA - TABLE Z-1 Limits for 260 mg/m3 Air Contaminants - 1910.1000 Skin notation C 1,000 ppm California permissible exposure limits for chemical contaminants (Title 8, Article 107)					
Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Danger of cutaneous absorption TWA 200 ppm USA. NIOSH Recommended Exposure Limits Potential for dermal absorption ST 250 ppm USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 200 ppm USA. Occupational Exposure Limits Potential for dermal absorption TWA 200 ppm USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants The value in mg/m3 is approximate. STEL 250 ppm USA. OSHA - TABLE Z-1 Limits for 325 mg/m3 Air Contaminants - 1910.1000 Skin notation TWA 200 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 Skin notation C 1,000 ppm California permissible exposure limits for chemical contaminants (Title 8, Article 107)					
(see BEI® section) Danger of cutaneous absorption TWA 200 ppm USA. NIOSH Recommended Exposure Limits Potential for dermal absorption ST 250 ppm USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 200 ppm USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 200 ppm USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants The value in mg/m3 is approximate. STEL 250 ppm USA. OSHA - TABLE Z-1 Limits for 325 mg/m3 Air Contaminants - 1910.1000 Skin notation TWA 200 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 Skin notation TWA 200 ppm USA. OSHA - TABLE Z-1 Limits for 260 mg/m3 Air Contaminants - 1910.1000 Skin notation C 1,000 ppm California permissible exposure limits for chemical contaminants (Title 8, Article 107)		,		Dialogical Exposure Index or Indiana	
Danger of cutaneous absorption TWA 200 ppm USA. NIOSH Recommended Exposure Limits Potential for dermal absorption ST 250 ppm USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 200 ppm USA. Occupational Exposure Limits Potential for dermal absorption TWA 200 ppm USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants The value in mg/m3 is approximate. STEL 250 ppm USA. OSHA - TABLE Z-1 Limits for 325 mg/m3 Air Contaminants - 1910.1000 Skin notation TWA 200 ppm USA. OSHA - TABLE Z-1 Limits for 260 mg/m3 Air Contaminants - 1910.1000 Skin notation C 1,000 ppm California permissible exposure limits for chemical contaminants (Title 8, Article 107)				a Biological Exposure index of indices	
TWA 200 ppm 260 mg/m3 USA. NIOSH Recommended Exposure Limits Potential for dermal absorption ST 250 ppm 325 mg/m3 Exposure Limits Potential for dermal absorption TWA 200 ppm USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 200 ppm USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants The value in mg/m3 is approximate. STEL 250 ppm USA. OSHA - TABLE Z-1 Limits for 325 mg/m3 Air Contaminants - 1910.1000 Skin notation TWA 200 ppm USA. OSHA - TABLE Z-1 Limits for 260 mg/m3 Air Contaminants - 1910.1000 Skin notation C 1,000 ppm California permissible exposure limits for chemical contaminants (Title 8, Article 107)		`	,	nn .	
Description					
Potential for dermal absorption ST 250 ppm USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 200 ppm USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants The value in mg/m3 is approximate. STEL 250 ppm USA. OSHA - TABLE Z-1 Limits for 325 mg/m3 Air Contaminants - 1910.1000 Skin notation TWA 200 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 Skin notation TWA 200 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 Skin notation C 1,000 ppm California permissible exposure limits for chemical contaminants (Title 8, Article 107)					
325 mg/m3 Exposure Limits		Potential for	dermal absorption		
Potential for dermal absorption TWA		ST			
TWA 200 ppm USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants The value in mg/m3 is approximate. STEL 250 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 Skin notation TWA 200 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 Skin notation TWA 200 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 Skin notation C 1,000 ppm California permissible exposure limits for chemical contaminants (Title 8, Article 107)					
260 mg/m3					
Contaminants The value in mg/m3 is approximate. STEL 250 ppm USA. OSHA - TABLE Z-1 Limits for 325 mg/m3 Air Contaminants - 1910.1000 Skin notation TWA 200 ppm USA. OSHA - TABLE Z-1 Limits for 260 mg/m3 Air Contaminants - 1910.1000 Skin notation C 1,000 ppm California permissible exposure limits for chemical contaminants (Title 8, Article 107)		TWA			
STEL 250 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 Skin notation TWA 200 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 Skin notation C 1,000 ppm California permissible exposure limits for chemical contaminants (Title 8, Article 107)			260 mg/m3		
STEL 250 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 Skin notation TWA 200 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 Skin notation C 1,000 ppm California permissible exposure limits for chemical contaminants (Title 8, Article 107)					
Skin notation TWA 200 ppm USA. OSHA - TABLE Z-1 Limits for 260 mg/m3 Air Contaminants - 1910.1000 Skin notation C 1,000 ppm California permissible exposure limits for chemical contaminants (Title 8, Article 107)		STEL			
TWA 200 ppm USA. OSHA - TABLE Z-1 Limits for 260 mg/m3 Air Contaminants - 1910.1000 Skin notation C 1,000 ppm California permissible exposure limits for chemical contaminants (Title 8, Article 107)				Air Contaminants - 1910.1000	
260 mg/m3 Air Contaminants - 1910.1000 Skin notation C 1,000 ppm California permissible exposure limits for chemical contaminants (Title 8, Article 107)			,		
C 1,000 ppm California permissible exposure limits for chemical contaminants (Title 8, Article 107)			260 mg/m3		
limits for chemical contaminants (Title 8, Article 107)		Skin notation			
(Title 8, Article 107)		С	1,000 ppm		
		Skin			

Sigma-Aldrich - 70720 Page 4 of 9

PEL	200 ppm 260 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
Skin		
STEL	250 ppm 325 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
Skin	·	

Hazardous components without workplace control parameters

Biological occupational exposure limits

Component	CAS-No.	Parameters	Value	Biological specimen	Basis
Methanol	67-56-1	Methanol	15.0000 mg/l	Urine	ACGIH - Biological Exposure Indices (BEI)
	Remarks	End of shift (A	End of shift (As soon as possible after exposure ceases)		
		Methanol	15 mg/l	Urine	ACGIH - Biological Exposure Indices (BEI)
		End of shift (As soon as possible after exposure ceases)			

8.2 Exposure controls

Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

Personal protective equipment

Eye/face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact

Material: Nitrile rubber

Minimum layer thickness: 0.11 mm Break through time: 480 min

Material tested:Dermatril® (KCL 740 / Aldrich Z677272, Size M)

Splash contact

Material: Nitrile rubber

Minimum layer thickness: 0.11 mm Break through time: 480 min

Material tested:Dermatril® (KCL 740 / Aldrich Z677272, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Body Protection

Complete suit protecting against chemicals, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face particle respirator type N99 (US) or type P2 (EN 143) respirator cartridges as a backup to engineering controls. If the respirator is the

Sigma-Aldrich - 70720 Page 5 of 9

sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Form: crystalline a) Appearance

Colour: beige

Odour No data available b) No data available Odour Threshold c) d) No data available

Melting point/freezing

point

Melting point/range: 196 - 199 °C (385 - 390 °F)

Initial boiling point and

boiling range

No data available

No data available g) Flash point No data available h) Evaporation rate i) Flammability (solid, gas) No data available Upper/lower j)

flammability or explosive limits No data available

Vapour pressure No data available Vapour density No data available No data available m) Relative density n) Water solubility No data available

Partition coefficient: noctanol/water

No data available

Auto-ignition temperature

No data available

Decomposition temperature

No data available

Viscosity No data available Explosive properties No data available Oxidizing properties No data available

9.2 Other safety information

No data available

10. STABILITY AND REACTIVITY

Reactivity

No data available

10.2 **Chemical stability**

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

No data available

10.4 Conditions to avoid

No data available

10.5 Incompatible materials

Strong oxidizing agents

10.6 Hazardous decomposition products

Hazardous decomposition products formed under fire conditions. - Carbon oxides, Nitrogen oxides (NOx), Hydrogen chloride gas

Other decomposition products - No data available

In the event of fire: see section 5

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity

No data available

Inhalation: No data available Dermal: No data available

No data available

Skin corrosion/irritation

No data available

Serious eye damage/eye irritation

No data available

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as

probable, possible or confirmed human carcinogen by IARC.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a

known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a

carcinogen or potential carcinogen by OSHA.

Reproductive toxicity

No data available No data available

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

Additional Information

RTECS: Not available

Effects due to ingestion may include:, Nausea, Headache, Vomiting, Gastrointestinal disturbance, Dizziness, Weakness, Confusion., Drowsiness

Stomach - Irregularities - Based on Human Evidence

Stomach - Irregularities - Based on Human Evidence (Methanol)

Sigma-Aldrich - 70720 Page 7 of 9

12. ECOLOGICAL INFORMATION

12.1 Toxicity

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Other adverse effects

No data available

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Product

Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material. Dissolve or mix the material with a combustible solvent and burn in a chemical incinerator equipped with an afterburner and scrubber.

Contaminated packaging

Dispose of as unused product.

14. TRANSPORT INFORMATION

DOT (US)

Not dangerous goods

IMDG

Not dangerous goods

ΙΔΤΔ

Not dangerous goods

15. REGULATORY INFORMATION

SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Components

The following components are subject to reporting levels established by SARA Title III, Section 313:

 CAS-No.
 Revision Date

 Methanol
 67-56-1
 2007-07-01

SARA 311/312 Hazards

Acute Health Hazard, Chronic Health Hazard

Massachusetts Right To Know Components

Methanol CAS-No. Revision Date 67-56-1 2007-07-01

Pennsylvania Right To Know Components

N-2-Aminoethyl-1-naphthylamine dihydrochloride
Methanol

CAS-No. Revision Date
1465-25-4
67-56-1
2007-07-01

New Jersey Right To Know Components

CAS-No. Revision Date

Sigma-Aldrich - 70720 Page 8 of 9

N-2-Aminoethyl-1-naphthylamine dihydrochloride 1465-25-4

Methanol 67-56-1 2007-07-01

California Prop. 65 Components

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive 67-56-1 Revision Date 2012-03-16

harm. Methanol

16. OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3.

Acute Tox. Acute toxicity
Eye Irrit. Eye irritation
Flam. Liq. Flammable liquids

H225 Highly flammable liquid and vapour.

H301 + H311 + Toxic if swallowed, in contact with skin or if inhaled

H331

H302 Harmful if swallowed.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H370 Causes damage to organs.

Skin Irrit. Skin irritation

STOT SE Specific target organ toxicity - single exposure

HMIS Rating

Health hazard: 2
Chronic Health Hazard: *
Flammability: 0
Physical Hazard 0

NFPA Rating

Health hazard: 2
Fire Hazard: 0
Reactivity Hazard: 0

Further information

Copyright 2016 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Preparation Information

Sigma-Aldrich Corporation Product Safety – Americas Region 1-800-521-8956

Version: 3.13 Revision Date: 09/23/2016 Print Date: 11/02/2018

Sigma-Aldrich - 70720 Page 9 of 9